

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

LPSRK30SP 30A 600V TD Dual Elem Class RK1 Low Peak Fuse Bussmann Fuses

Catalog Number	LPSRK30SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK1 Fuse, LPS-RK, Time-Delay, Dual-Element, Current Limiting Fuse, 30 A, Non-Indicating Fuse, Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	
Product Category	Dual Element
eatures	
amperage rating	30
connection	Ferrule End X Ferrule End
dimensions	5.0000 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	Class RK1
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
media	Yes
Response Time	8 S at 500%
Voltage Rating	600 Vac, 300 Vdc
imensions and Weight	
Size	0.81 In Diameter X 5.00 In Length
escriptions	
Description	30A 600V TD DUAL ELEM CLASS RK1 LOW PEAK FUSE
extra long description	BUSS LPS-RK-30SP LOW-PEAK DUAL ELEM
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann Series Class RK1 fuse, LPS-RK, time-delay, dual-element, current limiting fuse, 30 A, non-indicating fuse, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc
Product Type	Low-Peak Dual Element
Special Features	Electrically Isolated End Cap



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00051712548366
Manufacturers Part Number	LPS-RK-30SP
UPC	051712548366
Taxonomies, Classifications, and Cate	egories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.16
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked