

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

LR50M 1/2" LR FM5 Mall Iron Cond Body *Appleton/Oz Gedney*

LR50M
Appleton/Oz Gedney
Form 35 Unilets Type LR Conduit Outlet Body, Hub Size: 1/2 In, Form: 35, Length: 4.63 In, Width: 2 In, Material: Malleable Iron, Finish: Triple-Coat (Zinc Electroplate, Chromate and Epoxy Powder Coat), Connection: Tapered Female Threaded,
0.8100 (lbs/each)
Bodies & Covers
Tapered Female Threaded
35
Triple-Coat (Zinc Electroplate, Chromate And Epoxy Powder Coat)
1/2
4.63
2
1/2" LR FM5 MALL IRON COND BODY
APP LR50-M UNILET FORM 35 1/2 THR
Form 35 UNILETS Type LR Conduit Outlet Body, Hub Size: 1/2 IN, Form: 35, Length: 4.63 IN, Width: 2 IN, Material: Malleable Iron, Finish: Triple-Coat (Zinc Electroplate, Chromate And Epoxy Powder Coat), Connection: Tapered Female Threaded,
Unilet Form 35 1/2 THR (A)
Accurately tapped, tapered threads for tight, rigid joints and excellent ground continuity; Allow connections for branch runs; Connect and change direction of conduit runs; High tensile strength and ductility, high corrosion resistance, high impact and shock resistance; Make bends in conduit system; Permit access to conductors for maintenance; Provide openings for splicing; Serve as pulling fittings; Sizes with flat-back design ideal where fitting is mounted flat against surface; Smooth, rounded integral bushings
Appleton
00781381481458
LR50-M

781381481458



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, ar	nd Categories
Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Type LR Conduit Outlet Body
Packaging	
Carton	10
Package	50
Weight Per each	0.81
Uses, Certifications, and Stand	ards
Application	For Use With Rigid Steel, Rigid Aluminum Conduit And IMC
standard	UL 514A, UL 514B, UL File Number E2527, CSA C22.2 No. 18.3,

CSA 065183, NEMA FB-1