

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## LT112UL 1-1/2" Ua Sealtite Conduit, Bonded UI 50'

Southwire Company			
Catalog Number	LT112UL		
Manufacturer	Southwire Company		
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound Strip Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integral Copperbonding Strip Enclosed Within The Steel Convolutions. For 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild		
Weight per unit			
Product Category	Conduit & Raceways		
Features			
outside diameter	1882		
Dimensions and Weight			
Length	50		
Descriptions			
Description	1-1/2" UA SEALTITE CONDUIT, BONDED UL		
extra long description	SWC 55093205 Titan2 Type UL Liquidt		
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized steel. For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked steel strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild		
Product Type	TITAN2 Type UI Liquidtight Flexible Metal Conduit		
Manufacturer Information			
Brand	Flexible Conduit		
GTIN	00032886042355		
	55093205		
UPC	032886042355		
Taxonomies, Classifications, and (	<b>U</b>		
	Liquid Tight		
Туре	LTM-UL		
Trade Size			
Trade Size	1 1/2		



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability Status	Inactive	
Packaging	mactive	
Carton	50	
Weight Per each	1.12	