

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

700 Industry Way Suite 10 75078-0000, TX Prosper Phone: 469-899-3981 Fax: 469-899-3982



## LT12545 1-1/4" 45D LT Conn Crouse-Hinds

Catalog Number	LT12545
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC 45° Angle, Non-Insulated, Malleable Iron, 1-1/4"
Weight per unit	0.9500 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	3.5000 IN X 2.2500 IN X 3.5000 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	1-1/4" 45D LT CONN
extra long description	MIDWEST LT12545 1 1/4 LT 45 DEGREE
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are
	designed to protect conductors from mechanical damage due to
	vibration and movement while sealing out cutting oils, coolants,
	water, and dust. Typical applications include the wiring of
	machine tools, motors, transformers, food processing
	equipment, robotics, air conditioning units and illuminated signs.
	To meet any customer preference, Crouse-Hinds series
	liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC,
	45° angle, Non-insulated, Malleable iron, 1-1/4"
Product Type	1 1/4 LT 45 Degree Conn
Manufacturer Information	ç
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564451255
Manufacturers Part Number	LT12545
UPC	784564451255
Taxonomies, Classifications, and (	Categories
Category Description	METALLIC FITTINGS
Туре	
Trade Size	
Trade Size	1 1/4 in



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

700 Industry Way Suite 10 75078-0000, TX Prosper Phone: 469-899-3981 Fax: 469-899-3982

11001/0	
PARKA	
Packa	

Carton	5
Weight Per each	0.95
Uses, Certifications, and Sta	ndards
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.23