
 TECHNICAL DATA SHEET

Bullet® liquidtight fittings

Liquidtight flexible non-metallic conduit



01



02

 01
 straight LT38P black
 fitting

 02
 90° LT38P black fitting

Features:

- Connect assemblies to conduit without disassembly
- Designed to be installed with a positive installation criteria (gland bottoms on body shoulder)
- Rugged low profile non-metallic body and gland construction
- Captivated sealing “O” ring with predetermined compression for a reliable seal at enclosure
- Connector ferrule designed to accept variations in conduit inside diameter and is tolerant of field conduit cuts
- Designed to reduce friction between conduit I.D. and ferrule allowing conduit to seat properly for effective seal
- Easy installation
- Provides a double sealing action
- Elongated gland nut profile designed to provide additional strain relief for 90° pull and an easy hand grip
- Performance unaffected by exposure to detergents, cleaners, and sanitizers commonly encountered in food processing plants and tropical industrial environment.
- Performance unaffected by cutting fluids, wiring pulling compounds and Marine environment
- Meets industry standards for cold impact

Engineered to meet the demand for a tough, reusable, non metallic liquidtight fitting.

Certifications / Standards:


Applications:

- A series of non-metallic connectors designed to provide a liquidtight seal when terminating liquid-tight non-metallic conduit (UL Type B) or non-metallic tubing to a box or enclosure with knockout opening or a threaded hub

Conforms to:

- C.S.A. 22.2 No. 227.2 & No. 227.3
- ANSI/UL514B
- Watertight requirements of Type 4 and Type 6 enclosures
- Federal Standards H28 (NPT threads)

Material / Materials / Finishes

- Body Gland-Weather stabilized thermoplastic (black)
- “O” Ring - Nitrile (blue)
- Locknut - Steel/ electro zinc plated
- Matl. temp. rating - Thermoplastic - 40°C to 105°C
- Material Flammability Rating: UL94-V2

Temperature range:

- -18°C to +105°C (-2°F to +221°F)

Chemical resistance:

- See publication TDS000081

Technical Data:

Product selection and dimension

Drawing	Part No.**	Trade Size	Dimensions					
			A Inches ±0.15 (mm) ±0.40	B* Inches ±0.15 (mm) ±0.90	C Inches ±0.15 (mm) ±0.40	D min. Inches (mm)	E Thread NPT (ISO)	F** approx. Inches (mm)
LT38P series straight fittings								
	LT38P (-ISO20)	3/8"	.570 (14.48)	1.595 (40.51)	1.354 (34.39)	.417 (10.59)	1/2 - 14 (20)	-
	LT50P (-ISO20)	1/2"	.570 (14.48)	1.636 (41.55)	1.448 (36.78)	.550 (13.97)	1/2 - 14 (20)	-
	LT75P (-ISO25)	3/4"	.582 (14.78)	1.757 (44.63)	1.740 (44.20)	.740 (18.80)	3/4 - 14 (25)	-
	LT100P	1"	.726 (18.44)	1.923 (48.84)	2.068 (52.53)	.940 (23.88)	1 - 11 1/2	-
	LT125P	1 1/4"	.750 (19.05)	2.164 (54.97)	2.494 (63.35)	1.257 (31.93)	1 1/4 - 11 1/2	-
	LT150P	1 1/2"	.767 (19.48)	2.353 (59.77)	2.784 (70.71)	1.453 (36.91)	1 1/2 - 11 1/2	-
	LT200P	2"	.794 (20.17)	2.605 (66.17)	3.362 (85.39)	1.883 (47.83)	2 - 11 1/2	-
LT38P series 45° fittings								
	LT438P	3/8"	.570 (14.48)	2.012 (51.10)	1.354 (34.39)	.417 (10.59)	1/2 - 14 (20)	1.534 (38.96)
	LT450P	1/2"	.570 (14.48)	2.092 (53.14)	1.448 (36.78)	.550 (13.97)	1/2 - 14 (20)	1.590 (40.39)
	LT475P	3/4"	.582 (14.78)	2.452 (62.28)	1.740 (44.20)	.740 (18.80)	3/4 - 14 (25)	1.821 (46.25)
	LT4100P	1"	.726 (18.44)	2.684 (68.17)	2.068 (52.53)	.940 (23.88)	1 - 11 1/2	2.034 (51.66)
	LT4125P	1 1/4"	.750 (19.05)	3.264 (82.91)	2.494 (63.35)	1.257 (31.93)	1 1/4 - 11 1/2	2.385 (60.58)
	LT4150P	1 1/2"	.767 (19.48)	3.605 (91.57)	2.784 (70.71)	1.453 (36.91)	1 1/2 - 11 1/2	2.604 (66.14)
	LT4200P	2"	.794 (20.17)	4.210 (106.93)	3.362 (85.39)	1.883 (47.83)	2 - 11 1/2	3.050 (77.47)
LT38P series 90° fittings								
	LT938P (-ISO20)	3/8"	.570 (14.48)	1.380 (35.05)	1.354 (34.39)	.417 (10.59)	1/2 - 14 (20)	1.880 (47.75)
	LT950P (-ISO20)	1/2"	.570 (14.48)	1.489 (37.82)	1.448 (36.78)	.550 (13.97)	1/2 - 14 (20)	1.986 (50.44)
	LT975P (-ISO25)	3/4"	.582 (14.78)	1.790 (45.47)	1.740 (44.20)	.740 (18.80)	3/4 - 14 (25)	2.212 (56.18)
	LT9100P	1"	.726 (18.44)	2.104 (53.44)	2.068 (52.53)	.940 (23.88)	1 - 11 1/2	2.508 (63.70)
	LT9125P	1 1/4"	.750 (19.05)	2.564 (65.13)	2.494 (63.35)	1.257 (31.93)	1 1/4 - 11 1/2	2.856 (72.54)
	LT9150P	1 1/2"	.767 (19.48)	2.854 (72.49)	2.784 (70.71)	1.453 (36.91)	1 1/2 - 11 1/2	3.144 (79.86)
	LT9200P	2"	.794 (20.17)	3.432 (87.17)	3.362 (85.39)	1.883 (47.83)	2 - 11 1/2	3.675 (93.34)

Note: Product must be installed in accordance with applicable national and local electrical codes.
 ** Fittings with ISO threads will have the ISO threaded suffix as part of the catalog number. (Example: LT938PISO20)
 * After assembly

ABB Installation Products Inc.
 Memphis, Tennessee
 tnb.abb.com
 USA

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. (Formerly Thomas & Betts Corp.) does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction – in whole or in part – is forbidden without prior written consent of ABB Installation Products Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved.



Let's write the future.
 Together. **abb.com**