

## ELLIOTT ELECTRIC SUPPLY No Deliver Lower Cost. Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## LT30045G 3" 45D LT Conn Ground 1/0 Crouse-Hinds

Catalog Number	LT30045G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC 45° Angle, Aluminum Ground Lug, Non-Insulated, #1/0-8 Awg Lug Size, Malleable Iron, 3"
Weight per unit	
Product Category	Liquid Tight Fittings
eatures	
connection	Threaded
dimensions	8.7500 IN X 4.1900 IN X 8.7500 IN
installation type	THREADED
Vaterial, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	3" 45D LT CONN GROUND 1/0
extra long description	MIDWEST LT30045G 3 LT 45 DEGREE CON
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC 45° angle, Aluminum ground lug, Non-insulated, #1/0-8 AWG lug size, Malleable iron, 3"
Product Type	3 LT 45 Degree Conn GRND 1/0
Special Features	
Vanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564260284
Manufacturers Part Number	
UPC	70457402004
axonomies, Classifications, and	Categories
Category Description	

ourcegory bescription	ME MEETO TITIII 000
Туре	Liquidtight connector



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

Trade Size Trade Size	3 in		
Packaging Carton	1		
Weight Per each	8.3		
Uses, Certifications, and Standards			
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other		
standard	UL 467, UL 514B, CSA C22.40		