

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## LT38 3/8" STR LT Steel Conn Crouse-Hinds

Catalog Number	LT38
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC
	Straight, Non-Insulated, Malleable Iron, 3/8"
Weight per unit	0.1600 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	1.6300 IN X 1.1300 IN X 1.1300 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	3/8" STR LT STEEL CONN
extra long description	MIDWEST LT38 3/8 LT CONN
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are
	designed to protect conductors from mechanical damage due to
	vibration and movement while sealing out cutting oils, coolants,
	water, and dust. Typical applications include the wiring of
	machine tools, motors, transformers, food processing
	equipment, robotics, air conditioning units and illuminated signs To meet any customer preference, Crouse-Hinds series
	liquidtight fittings are available in a variety sizes, configurations
	and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC,
	Straight, Non-insulated, Malleable iron, 3/8"
Product Type	3/8 LT Conn
Manufacturer Information	
Brand	Eaton
GTIN	00784564300386
Manufacturers Part Number	LT38
UPC	784564300386
Taxonomies, Classifications, and	Categories
Category Description	
Туре	Liquidtight connector
Trade Size	
Trade Size	3/8 in



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Packaging

Carton	25
Weight Per each	0.16
Uses, Certifications, and Standards	6
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.2