

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LT40045 4" 45D LT Conn Crouse-Hinds

Catalog Number	LT40045	
Manufacturer	Crouse-Hinds	
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC,	
	45° Angle, Non-Insulated, Malleable Iron, 4"	
Weight per unit	15.9 (lbs/each)	
Product Category	Liquid Tight Fittings	
Features		
connection	Threaded	
dimensions	12.3100 IN X 5.7500 IN X 12.3100 IN	
installation type	THREADED	
Material, Color, and Finish		
Color	MALLEABLE IRON	
Descriptions		
Description	4" 45D LT CONN	
extra long description	MIDWEST LT40045 4 LT 45 DEGREE CONN	
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are	
	designed to protect conductors from mechanical damage due to	
	vibration and movement while sealing out cutting oils, coolants,	
	water, and dust. Typical applications include the wiring of	
	machine tools, motors, transformers, food processing	
	equipment, robotics, air conditioning units and illuminated signs.	
	To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations	
	and materials, inclu	
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC,	
5	45° angle, Non-insulated, Malleable iron, 4"	
Product Type	4 LT 45 Degree Conn	
Manufacturer Information		
Brand	Eaton	
GTIN	00784564454003	
Manufacturers Part Number	LT40045	
UPC	784564454003	
Taxonomies, Classifications, and C	ategories	
Category Description		
Туре		
Trade Size		
Trade Size	4 in	



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pacl		
Pari	k an	Ind
I UU	\uu	IIIM

гаскаушу	
Carton	1
Weight Per each	15.9
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.47