

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**Trade Size** 

Trade Size

## LTB12590 1-1/4" 90D LT Conn

Catalog Number	LTB12590
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC
	90° Angle, Insulated, Malleable Iron, 1-1/4"
Weight per unit	
Product Category	Liquid Tight Fittings
tures	
connection	Threaded
dimensions	3.0600 IN X 2.2500 IN X 3.0600 IN
installation type	THREADED
terial, Color, and Finish	
Color	MALLEABLE IRON
criptions	
Description	1-1/4" 90D LT CONN
extra long description	MIDWEST LTB12590 1 1/4 LT 90 DEGREE
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are
reatures	designed to protect conductors from mechanical damage due to
	vibration and movement while sealing out cutting oils, coolants,
	water, and dust. Typical applications include the wiring of
	machine tools, motors, transformers, food processing
	equipment, robotics, air conditioning units and illuminated signs.
	To meet any customer preference, Crouse-Hinds series
	liquidtight fittings are available in a variety sizes, configurations
	and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC,
	90° angle, Insulated, Malleable iron, 1-1/4"
Product Type	1 1/4 LT 90 Degree Conn Insulated
nufacturer Information	
Brand	Eaton
GTIN	00784564911254
Manufacturers Part Number	LTB12590
UPC	784564911254
onomies, Classifications, and C	categories
Category Description	NASTALLIO SITTINIOS
Туре	

1 1/4 in



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Package	5
Weight Per each	0.0404
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.95