

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LTB5045 1/2" 45D LT Conn Ins Crouse-Hinds

Catalog Number	LTB5045
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Insulated, Malleable Iron, 1/2"
Weight per unit	0.3000 (lbs/each)
Product Category	Liquid Tight Fittings

Features

connection	Threaded
dimensions	2.5000 IN X 1.2500 IN X 2.5000 IN
installation type	THREADED

Material, Color, and Finish

Color MALLEAI	BLE IRON
---------------	----------

Descriptions

Description	1/2" 45D LT CONN INS
extra long description	MIDWEST LTB5045 1/2 LT 45 DEGREE CO
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Insulated, Malleable iron, 1/2"
Product Type	1/2 LT 45 Degree Conn Insulated

Manufacturer Information

Brand	Eaton
GTIN	00784564460509
Manufacturers Part Number	LTB5045
UPC	784564460509

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Liquidtight connector

Trade Size

Trade Size 1/2 in	
-------------------	--



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	25
Weight Per each	0.3
Uses, Certifications, and Star	ndards
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.81