

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LTB5045G 1/2" 45D LT Conn Crouse-Hinds

Crouse-Hinas	
Catalog Number	LTB5045G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Aluminum Ground Lug, Insulated, #4-14 Awg Lug Size, Malleable Iron, 1/2"
Weight per unit	0.3500 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	2.5000 IN X 1.2500 IN X 2.5000 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	1/2" 45D LT CONN
extra long description	MIDWEST LTB5045G 1/2 LT 45 DEG CONN
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Aluminum ground lug, Insulated, #4-14 AWG lug size, Malleable iron, 1/2"
Product Type	1/2 LT 45 Deg Conn Ground Lug Insulated
Special Features	With 14 To 4 AWG Aluminum Grounding Lug
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564264213
Mari Carl III David Maria	LTDEOAEC

Mar

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564264213
Manufacturers Part Number	LTB5045G
UPC	784564264213

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Liquidtight connector



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Trade Size	1/2 in
Packaging	
Carton	1
Package	25
Weight Per each	0.35
Uses, Certifications, and Standards	S
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.82