



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## M187075342 Heat Shrink Sleeve, 0.187 " Dia X 0.75", BK/WH

Brady Worldwide, Inc.

Catalog Number	M187075342
Manufacturer	Brady Worldwide, Inc.
Description	M Series Permasleeve® Heat-Shrink Polyolefin 20 Awg to 10 Awg BK/WH 80 Each
Weight per unit	0.2950 (lbs/each)
Product Category	CBL Marking & Labeling Equipt

### Features

Material	Heat-shrink Polyolefin
Number of Markers	80
Quantity	Cartridge of 80 Each
Shrink Ratio	3:1
Temperature Range	-67 °F - 275 °F
Wire Size	0.187 in Dia x 0.75 in W

### Material, Color, and Finish

Finish	Matte
Legend Color	Black on White

### Dimensions and Weight

Diameter	0.187
Height	0.335 in
Size	0.335 in H x 0.75 in W
Width	0.75 in

### Descriptions

Description	HEAT SHRINK SLEEVE, 0.187 " DIA X 0.75", BK/WH
extra long description	BRADY M-187-075-342 SLEEVE, 0.187 I
Features	Permanently mark wires with the durable PermaSleeve® PS heat-shrink polyolefin sleeve label material (B-342). Designed for use with a durable Brady handheld label printer.
Long Description	M Series PermaSleeve® Heat-shrink Polyolefin 20 AWG to 10 AWG BK/WH 80 Each
Product Type	Sleeve, 0.187 In Dia X 0.75 In W
Special Features	Heat Shrink

### Manufacturer Information

Brand	Brady®
GTIN	00662820999942
Manufacturers Part Number	M-187-075-342
UPC	662820999942



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description ..... WIRE LUBE, MARKERS, & TIES  
Type ..... SLEEVE

## Availability

Status ..... Inactive

## Packaging

Carton ..... 1  
Weight Per each ..... 0.295

## Uses, Certifications, and Standards

Application ..... Wire and Cable Labeling  
standard ..... ASTM D 2671;ASTM E 162;ASTM E 662;ASTM G  
155;MIL-STD-202;SAE-AMS-DTL-23053;SAE-AS-81531;UL  
Recognized