

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## M22DLRK01230R III Mom PB Sil-BZL FLSH Red 85-264VAC 1NC Eaton Corp

Catalog Number	M22DLRK01230R
Manufacturer	Eaton Corp
Description	Eaton M22 Modular Pushbutton, Complete Device, 22.5 MM, Flush, Momentary, Illuminated, Bezel: Silver, Button: Red, 1NC, IP67, IP69K, Nema 4X, 13, 85-264V
Weight per unit	0.0800 (lbs/each)
Product Category	Push Button Complete Assemblie
eatures	
actuator	Button, Flush
Contact Configuration	1 NC
Voltage Rating	
Dimensions and Weight	
Depth	1.46
Height	2.16
Size	22.5 mm
Width	1.18
escriptions	
Description	ILL MOM PB SIL-BZL FLSH RED 85-264VAC 1NC
extra long description	ETN M22-DL-R-K01-230R NEMA 4X, 13,
Features	This attractive, functional line of pushbuttons features a space-saving construction that enables fast assembly. The complete illuminated M22 line offers LED light units to ensure high-quality brightness and up to 100,000 hours of illumination Because of the rugged design of these pushbuttons, most operators and contact blocks exceed five million mechanical operations.
Long Description	Eaton M22 modular pushbutton, Complete Device, 22.5 mm, Flush, Momentary, Illuminated, Bezel: Silver, Button: Red, 1NC, IP67, IP69K, NEMA 4X, 13, 85-264V
Product Type	Nema 4X, 13, 85-264V
Special Features	M22 series
Manufacturer Information	
Brand	Eaton
GTIN	00786685274867
Manufacturers Part Number	M22-DL-R-K01-230R
Model	Modular pushbutton
UPC	786685274867



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	MINATURE PILOT DEVICES.22MM
Packaging Carton	1
Weight Per each	0.08
Uses, Certifications, and Standa	rds
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
environmental conditions	IP67, IP69K, NEMA 4X, NEMA 13
standard	CSA Certified,Lloyd's Register Certified,CCC Marked,GoST-R,CE Marked,Bureau Veritas