

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### M22DLY III Mom PB Sil-BZL FLSH Yel Eaton Corp

Catalog Number	M22DLY
Manufacturer	Eaton Corp
Description	Eaton M22 Modular Pushbutton, 22.5 MM, Flush, Momentary, Illuminated, Bezel: Silver, Button: Yellow, IP67, IP69K, Nema 4X 13, 5, 000, 000 Million Mechanical Operations
Weight per unit	0.1000 (lbs/each)
Product Category	Push Button Complete Assemblie
eatures	
actuator	Flush, Button
operating cycles	5 million
mensions and Weight	
Depth	1.17
Height	0.39
Size	
Width	1.17
escriptions	
Description	ILL MOM PB SIL-BZL FLSH YEL
extra long description	ETN M22-DL-Y ILL MOM PB SIL-BZL FLS
Features	This attractive, functional line of pushbuttons features a
	space-saving construction that enables fast assembly. The
	complete illuminated M22 line offers LED light units to ensure
	high-quality brightness and up to 100,000 hours of illumination
	Because of the rugged design of these pushbuttons, most operators and contact blocks exceed five million mechanical
	operations.
Long Description	Eaton M22 modular pushbutton, 22.5 mm, Flush, Momentary,
	Illuminated, Bezel: Silver, Button: Yellow, IP67, IP69K, NEMA 4x
	13, 5,000,000 Million mechanical operations
Product Type	III Mom PB Sil-BZL FLSH Yel
Special Features	M22 series
anufacturer Information	
Brand	Eaton
GTIN	00786685274577
Manufacturers Part Number	M22-DL-Y
Model	Modular pushbutton
UPC	786685274577

#### **Taxonomies, Classifications, and Categories**

Category Description MINATURE PILOT DEVICES.22MM



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

			n	

Carton	1	
Weight Per each	0.1	

#### Uses, Certifications, and Standards

co, oci tilloatiolio, alla otaliaali	из
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels
	and EOEMs
environmental conditions	IP67, IP69K, NEMA 4X, NEMA 13
standard	CCC Marked,Lloyd's Register Certified,CSA Certified,Bureau
	Veritas,CE Marked,GoST-R