

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



M22SDHG Non-III Mom PB BLK-BZL Extd GRN Eaton Corp

Catalog Number	M22SDHG
Manufacturer	Eaton Corp
Description	Eaton M22 Modular Pushbutton M22 Modular Pushbutton Operator, 22.5 MM, Extended, Momentary, Non-Illuminated, Bezel: Black, Button: Green, IP67, IP69K, Nema 4X, 13, 5, 000, 000 Million Mechanical Operations
Weight per unit	0.0400 (lbs/each)
Product Category	Push Button Complete Assemblie
eatures	
actuator	Extended, Button
operating cycles	5 million
Dimensions and Weight	
Depth	1
Height	6
Size	22.5 mm
Width	5
Descriptions	
Description	NON-ILL MOM PB BLK-BZL EXTD GRN
extra long description	ETN M22S-DH-G NON-ILL MOM PB BLK-BZ
Features	This attractive, functional line of pushbuttons features a
	space-saving construction that enables fast assembly. The
	complete illuminated M22 line offers LED light units to ensure
	high-quality brightness and up to 100,000 hours of illumination. Because of the rugged design of these pushbuttons, most
	operators and contact blocks exceed five million mechanical
	operations.
Long Description	Eaton M22 modular pushbutton M22 Modular Pushbutton
	Operator, 22.5 mm, Extended, Momentary, Non-illuminated,
	Bezel: Black, Button: Green, IP67, IP69K, NEMA 4x, 13, 5,000,000
	Million mechanical operations
Product Type	Non-III Mom PB BLK-BZL Extd GRN
Anufacturer Information	
Brand	Eaton
GTIN	00786685275413
Manufacturers Part Number	M22S-DH-G
Model	Modular pushbutton
UPC	786685275413



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	MINATURE PILOT DEVICES.22MM
Packaging	
Carton	1
Weight Per each	0.04
Uses, Certifications, and Standa	rds
Application	Stationary Machinery and Equipment Outside Factory -
	Stationary Machinery and Equipment Outside Factory - Other
environmental conditions	IP67, IP69K, NEMA 4X, NEMA 13
standard	Lloyd's Register Certified,CSA Certified,CCC
	Marked, GoST-R, CE Marked, Bureau Veritas