

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





MACL153MBR Maestro 150W Led Multi Brown

Editori	
Catalog Number	MACL153MBR
Manufacturer	Lutron
Description	Maestro Led+ Multiloc, Ed Box Brown
Weight per unit	0.4000 (lbs/each)
Product Category	Lighting Dimmers
Features	
actuator	Tapswitch
connection	Screw Terminal
Connection Type	Screw Terminal
insulation	Plastic
Material	Plastic/Metal
Poles	1
Switch Type	Tapswitch

Switch Type 120 Voltage Rating

Wattage 600.000000000000000

Material, Color, and Finish

Color Brown

Dimensions and Weight

Size 4.69 x 2.94;119 x 75

Descriptions

criptions	
Description	MAESTRO 150W LED MULTI BROWN
extra long description	LUT MACL-153M-BR MAESTRO LED+ MULTI
Features	The Maestro LED+ dimmer switch provides optimal dimming
	performance of LED bulbs. This dimmer switch works with up to
	150-Watt of dimmable LED/CFL or 600-Watt of
	incandescent/halogen, allowing you to control multiple bulb
	types on the same circuit. It is designed to control a broad range
	of dimmable LED and CFL bulbs from a variety of brands including
	Philips, Cree, GE, EcoSmart and Lighting Science. Use the rocker
	to adjust the light level for any activity or set the preset level to
	ensure lights always t
Long Description	Maestro LED+ Multiloc, Ed Box Brown
Product Type	Maestro Led+ Multiloc Ed Box Brown
Special Features	Controls dimmable 150 W LED/CFL (screw-base) or 600 W
•	incandescent/halogen loads. Provides true dimming from each

location (with companion dimmers). Provides reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents.



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Inform

Brand	Lutron
GTIN	00784276010719
Manufacturers Part Number	MACL-153M-BR
UPC	784276010719

Taxonomies, Classifications, and Categories

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Digital fade dimmer, multi-location/3-way/single-pole

Packaging

Carton	1
Weight Per each	0.4

Uses, Certifications, and Standards

Application	Lighting Control
Enclosure	Plastic
environmental conditions	0 to 90% humidity, non-condensing. Indoor use only.
Frequency Rating	50 to 60
Mounting	WALLBOX
Operating Temperature	32 to 104
standard	UL, CSA, NOM