

ELLIOTT ELECTRIC SUPPLY No Doliver Lower Cost. Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

MLT4HLP Steel-Ty*	Stra
Panduit Corporation	

Catalog Number	MLT4HLP
Manufacturer	Panduit Corporation
Description	The MLT4H-LP Self-Locking Cable Tie Speeds Up Installation With
·	A Unique Self-Locking Head Design That Locks Into Place At Any
	Part Of The Tie Body. The Smooth Surfaces and Rounded Edges
	Assure Cable Protection and Worker Safety While Providing A
	Strong, Durable Method Of Cabling Bundle. The MLT4H-LP Cable
	Tie Can Be Used In A Wide Range Of Indoor, Outdoor, and
	Underground Applications. Color Stainless Steel.
Weight per unit	0.8014 (lbs/each)
Product Category	Cable Ties & Wraps
atures	
media	Yes
Tensile Strength	450
mensions and Weight	
Length	14.3
escriptions	
Description	STEEL-TY* STRA
extra long description	PAN MLT4H-LP Pan-Steel [®] MLT4H-LP Ca
Long Description	The MLT4H-LP self-locking cable tie speeds up installation with a
	unique self-locking head design that locks into place at any part
	of the tie body. The smooth surfaces and rounded edges assure
	cable protection and worker safety while providing a strong,
	durable method of cabling bundle. The MLT4H-LP cable tie can
	be used in a wide range of indoor, outdoor, and underground applications. Color Stainless Steel.
Product Type	Pan-Steel® MLT4H-LP Cable Tie, SS 304, Heavy, 4" Dia., PK50
Special Features	5
anufacturer Information	
Brand	Panduit®
GTIN	00074983543878
Marco Carl I and David Nilarda a	MLT4H-LP
UPC	074983543878
xonomies, Classifications, and (Categories
	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
	······································



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	50	
Package	250	
Weight Per each	0.8014	

Uses, Certifications, and Standards

Application	General
standard	UL E56854,CE,ABS,GL,SAE,BV,LR,DNV,USCG