



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

6510 Broadway St  
77554-0000, TX Galveston  
Phone: 409-741-0072  
Fax: 409-741-0433



## MLTFC6EHL316 23.4" SS6 Poly Coated BLK CBL Tie W/Self LCK Head *Panduit Corporation*

Catalog Number	MLTFC6EHL316
Manufacturer	Panduit Corporation
Description	Pan-Steel® Polyester Fully Coated Cable Ties Speed Up Installation With A Unique Self-Locking Head Design That Locks Into Any Part Of The Tie. Plus, 316 Stainless Steel Is Wrapped In Uv-Resistant, Halogen-Free, Low-Smoke Polyester to Promote Worker Safety and Reliability In Corrosive, High-Vibration, Temperature-Extreme Environments. Extra-Heavy Cross Section, Max Bundle Diameter: 6.0IN, 23.4IN, Tensile Strength: 1335, Black, 50PC.
Weight per unit	0.0521 (lbs/each)
Product Category	Cable Ties & Wraps

### Features

Tensile Strength	300
------------------	-----

### Dimensions and Weight

Length	23.4
Thickness	NA

### Descriptions

Description	23.4" SS6 POLY COATED BLK CBL TIE W/SELF LCK HEAD
extra long description	PAN MLTFC6EH-LP316 Pan-Steel® MLTFC
Long Description	Pan-Steel® Polyester Fully Coated Cable Ties speed up installation with a unique self-locking head design that locks into any part of the tie. Plus, 316 stainless steel is wrapped in UV-resistant, halogen-free, low-smoke Polyester to promote worker safety and reliability in corrosive, high-vibration, temperature-extreme environments. Extra-heavy cross section, Max bundle diameter: 6.0in, 23.4in, Tensile strength: 1335, Black, 50pc.
Product Type	Pan-Steel® MLTFC6EH-LP316 Cable Tie, Pet Coated SS 316, Blac
Special Features	Harsh

### Manufacturer Information

Brand	PANDUIT
GTIN	00074983446407
Manufacturers Part Number	MLTFC6EH-LP316
UPC	074983446407

### Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type	Cable Tie



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

6510 Broadway St  
77554-0000, TX Galveston  
Phone: 409-741-0072  
Fax: 409-741-0433

## Availability

minimum qty ..... 50 .....

## Packaging

Carton ..... 1 .....

Package ..... 50 .....

Weight Per each ..... 0.0521 .....

## Uses, Certifications, and Standards

Application ..... Corrosive Environment .....

standard ..... CE,ABS,UL .....