





GE  
Lighting

## 10389 - MVR1000U/BT37/PA

GE Multi-Vapor® PulseArc® Quartz Metal Halide BT37



### CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

#### Caution

- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use excessive force when installing lamp.
  - Do not use lamp if outer glass is scratched or broken.

#### Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
  - Do not exceed rated voltage.
  - Do not turn on lamp until fully installed.
  - Do not use beyond rated life.
  - Do not use lamp if outer glass is scratched or broken.
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - If used on a dimming system, see instructions.
  - Operate lamp only in specified position.
  - Turn lamp off at least once for 15 minutes per week.
  - Use in enclosed fixture rated for this product.
  - Use only properly rated ballast.
- A damaged lamp emits UV radiation which may cause eye/skin injury
  - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Do not turn on lamp until fully installed.
- Risk of Electric Shock
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - Turn power off before inspection, installation or removal.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in fixture rated for this product.

### GRAPHS & CHARTS

Graphs\_Spectral Power Distribution

### GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Quartz Metal Halide
Bulb	BT37
Base	Mogul Screw (E39)
Bulb Finish	Clear
Rated Life (Vert)	12000.0 h
Rated Life (Hor)	9000.0 hrs
Bulb Material	9000.0 h
Lamp Enclosure Type (LET)	Hard glass
Base Temperature (MAX)	Enclosed fixtures only
Bulb Temperature (MAX)	250.0 °C
LEED-EB MR Credit	430.0 °C
	139 picograms Hg per mean lumen hour

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (Vert)	115000.0
Initial Lumens	115000.0 /105000.0
Initial Lumens (Hor)	105000.0
Mean Lumens (Vert)	90000.0
Mean Lumens (Hor)	82000.0
Nominal Initial Lumens per Watt	105 /115
Color Temperature	3900.0 K
Color Rendering Index (CRI)	65.0

### ELECTRICAL CHARACTERISTICS


Wattage	1000.0
Burn Position	Universal burning position
Warm Up Time to 90% (MIN)	2.0 min
Warm Up Time to 90% (MAX)	5.0 min
Hot Restart Time to 90% (MIN)	10.0 min
Hot Restart Time to 90% (MAX)	15.0 min

### DIMENSIONS

Maximum Overall Length (MOL)	11.5000 in(292.1 mm)
Bulb Diameter (DIA) (MAX)	4.625 in(117.5 mm)
Bulb Diameter (DIA)	4.625 in(117.5 mm)
Light Center Length (LCL)	7.000 in(177.8 mm)

### PRODUCT INFORMATION

Product Code	10389
Description	MVR1000U/BT37/PA
ANSI Code	M141
Standard Package	Case
Standard Package GTIN	10043168103890
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168103893



**NOTES**



- When operated on a 120 hrs. cycle (minimum), lamp life rating may be extended by up to 50% based on engineering estimates.



GE  
Lighting

## 10389 - MVR1000U/BT37/PA

GE Multi-Vapor® PulseArc® Quartz Metal Halide BT37



### CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

#### Caution

- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use excessive force when installing lamp.
  - Do not use lamp if outer glass is scratched or broken.

#### Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
  - Do not exceed rated voltage.
  - Do not turn on lamp until fully installed.
  - Do not use beyond rated life.
  - Do not use lamp if outer glass is scratched or broken.
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - If used on a dimming system, see instructions.
  - Operate lamp only in specified position.
  - Turn lamp off at least once for 15 minutes per week.
  - Use in enclosed fixture rated for this product.
  - Use only properly rated ballast.
- A damaged lamp emits UV radiation which may cause eye/skin injury
  - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Do not turn on lamp until fully installed.
- Risk of Electric Shock
  - Do not use where directly exposed to water or outdoors without an enclosed fixture.
  - Turn power off before inspection, installation or removal.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in fixture rated for this product.

### GRAPHS & CHARTS

Graphs\_Spectral Power Distribution

### GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Quartz Metal Halide
Bulb	BT37
Base	Mogul Screw (E39)
Bulb Finish	Clear
Rated Life (Vert)	12000.0 h
Rated Life (Hor)	9000.0 hrs
Bulb Material	9000.0 h
Lamp Enclosure Type (LET)	Hard glass
Base Temperature (MAX)	Enclosed fixtures only
Bulb Temperature (MAX)	250.0 °C
LEED-EB MR Credit	430.0 °C
	139 picograms Hg per mean lumen hour

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (Vert)	115000.0
Initial Lumens	115000.0 /105000.0
Initial Lumens (Hor)	105000.0
Mean Lumens (Vert)	90000.0
Mean Lumens (Hor)	82000.0
Nominal Initial Lumens per Watt	105 /115
Color Temperature	3900.0 K
Color Rendering Index (CRI)	65.0

### ELECTRICAL CHARACTERISTICS


Wattage	1000.0
Burn Position	Universal burning position
Warm Up Time to 90% (MIN)	2.0 min
Warm Up Time to 90% (MAX)	5.0 min
Hot Restart Time to 90% (MIN)	10.0 min
Hot Restart Time to 90% (MAX)	15.0 min

### DIMENSIONS

Maximum Overall Length (MOL)	11.5000 in(292.1 mm)
Bulb Diameter (DIA) (MAX)	4.625 in(117.5 mm)
Bulb Diameter (DIA)	4.625 in(117.5 mm)
Light Center Length (LCL)	7.000 in(177.8 mm)

### PRODUCT INFORMATION

Product Code	10389
Description	MVR1000U/BT37/PA
ANSI Code	M141
Standard Package	Case
Standard Package GTIN	10043168103890
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168103893



**NOTES**

- When operated on a 120 hrs. cycle (minimum), lamp life rating may be extended by up to 50% based on engineering estimates.