

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



N250SP 250 Al/Cu Split Bolt *Nsi Industries*

N250SP
Nsi Industries
All Purpose Split Bolt Connector 250 MCM All Purpose Split Bolt Connectors Are Used For Combinations Of Aluminum to Copper, Aluminum to Aluminum, Steel to Aluminum, Copper to Copper, and Steel to Copper Applications. They Have An Electro-Tinned Body. UI Listed For Copper and Copperweld Wires Only. Includes Nut, Spacer and Pressure Pad.
0.5700 (lbs/each)
Large Terminals & Connectors
TIN PLATED COPPER
2
1
600 V
1 YEAR
1/0 STR - 250 MCM
Class A & B
Tin Plated Copper
Tin Plated Copper
L=2.106 - W=1.102



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_	•		
11000	rin	TIO	nc
Desc		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	117
-			

Description	250 AL/CU SPLIT BOLT
extra long description	NSI N-250SP Copper Split Bolt 2/0 T
Features	All Purpose Split Bolt Connector 250 MCM All Purpose Split Bolt Connectors are used for combinations of aluminum to copper, aluminum to aluminum, steel to aluminum, copper to copper, and steel to copper applications. They have an electro-tinned body. UL listed for copper and copperweld wires only. Includes nut, spacer and pressure pad.
Long Description	All Purpose Split Bolt Connector 250 MCM All Purpose Split Bolt Connectors are used for combinations of aluminum to copper, aluminum to aluminum, steel to aluminum, copper to copper, and steel to copper applications. They have an electro-tinned body. UL listed for copper and copperweld wires only. Includes nut, spacer and pressure pad.
Product Type	Copper Split Bolt 2/0 Tin Plated
Special Features	1/0 SOL-250 MCM - 6 Pack

Manufacturer Information

Brand	NSi
GTIN	00662381020390
Manufacturers Part Number	N-250SP
UPC	662381020390

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Туре	Tin Plated Copper Split Bolt

Packaging

Carton	1	
Package	6	
Weight Per each	0.57	

Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486B
Temperature Rating	90 C