


## 45° Non-Metallic Connectors




For use with non-metallic liquid-tight conduit, type B only. 45° connector provides a smooth, gradual radius bend. Wiring is easily pulled or pushed through fitting and there are no sharp edges to strip wire. Produced from UV rated plastic for long outdoor life.

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|
| NMLT4538       | 54538                    | 3/8        | 1/2     | 10       | 50      | 1.550 | .562  | 1.862 |
| NMLT4550       | 54550                    | 1/2        | 1/2     | 10       | 50      | 1.596 | .562  | 1.975 |
| NMLT4575       | 54575                    | 3/4        | 3/4     | 10       | 50      | 1.820 | .545  | 2.237 |
| NMLT45100      | 54110                    | 1          | 1       | 5        | 25      | 2.200 | .630  | 2.990 |
| NMLT45125      | 54125                    | 1-1/4      | 1-1/4   | 5        | 25      | 2.710 | .645  | 3.420 |
| NMLT45150      | 54150                    | 1-1/2      | 1-1/2   | 2        | 10      | 2.960 | .660  | 3.675 |
| NMLT45200      | 54200                    | 2          | 2       | 2        | 10      | 3.500 | .670  | 4.060 |

Add suffix "BL" to Catalog # when ordering in black, for example NMLT4550BL.



## 45° Non-Metallic Connectors



For use with non-metallic liquid-tight conduit, type B only. 45° connector provides a smooth, gradual radius bend. Wiring is easily pulled or pushed through fitting and there are no sharp edges to strip wire. Produced from UV rated plastic for long outdoor life.

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|
| NMLT4538       | 54538                    | 3/8        | 1/2     | 10       | 50      | 1.550 | .562  | 1.862 |
| NMLT4550       | 54550                    | 1/2        | 1/2     | 10       | 50      | 1.596 | .562  | 1.975 |
| NMLT4575       | 54575                    | 3/4        | 3/4     | 10       | 50      | 1.820 | .545  | 2.237 |
| NMLT45100      | 54110                    | 1          | 1       | 5        | 25      | 2.200 | .630  | 2.990 |
| NMLT45125      | 54125                    | 1-1/4      | 1-1/4   | 5        | 25      | 2.710 | .645  | 3.420 |
| NMLT45150      | 54150                    | 1-1/2      | 1-1/2   | 2        | 10      | 2.960 | .660  | 3.675 |
| NMLT45200      | 54200                    | 2          | 2       | 2        | 10      | 3.500 | .670  | 4.060 |

Add suffix "BL" to Catalog # when ordering in black, for example NMLT4550BL.

