

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



NMS3 12-14AWG NM 3 CNDTR W/GRND Splice Kit Nsi Industries

NMS3
Nsi Industries
Non Metallic Splice Kit 12-14 Awg For 3 Conductors With Ground Non Metallic Splice Kits Are Used For Splicing 12 or 14 Awg Solid Conductor, 3-Conductor Cable With Ground. Hinged Cover Makes Termination Fast and Easy. Approved For Use In A Variety Of Applications Including: Residential Branch Circuits, Manufactured Housing and Pre-Fabricated Building Structures.
0.1060 (lbs/each)
Splicing & Terminating Kits
splicing & reminating Kits
20 Amp
Thermoplastic
3
1
300 V
1 YEAR
12-14 AWG
3 Conductor With Ground
White
Thermoplastic
12-14AWG NM 3 CNDTR W/GRND SPLICE KIT
NSI NMS-3 Non Metallic Splice Kit 1
Non Metallic Splice Kit 12-14 AWG for 3 Conductors with Ground
Non Metallic Splice Kits are used for splicing 12 or 14 AWG solid conductor, 3-conductor cable with ground. Hinged cover makes termination fast and easy. Approved for use in a variety of applications including: residential branch circuits, manufactured housing and pre-fabricated building structures.
Non Metallic Splice Kit 12-14 AWG for 3 Conductors with Ground Non Metallic Splice Kits are used for splicing 12 or 14 AWG solid conductor, 3-conductor cable with ground. Hinged cover makes termination fast and easy. Approved for use in a variety of applications including: residential branch circuits, manufactured housing and pre-fabricated building structures.
Non Metallic Splice Kit 12/3
Fast Reliable To Connect 12 And 14 AWG Circuits Using Non-Metallic Cable



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

NASSI	ufacture	r Intor	MATIAN
IVIALII	11411111		1114111111
IVIGII	aiustais		HILLIOII

Brand	NSi
GTIN	00662381003218
Manufacturers Part Number	NMS-3
UPC	662381003218

Taxonomies, Classifications, and Categories

Category Description	SPLICE KITS
Type	Non-Metallic Cable Splices And Taps

Packaging

Carton	1	
.7.77.7.7.7.		
Weight Per each	0.106	

Uses, Certifications, and Standards

Application	NSI
standard	UL QAAV