

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



NNC37X37WH2 37MX37MMX2M WH Wire DCT

Panduit Corporation

Catalog Number	NNC37X37WH2	
Manufacturer	Panduit Corporation	
Description	The NNC37X37WH2 Halogen-Free Wide Slot Wiring Duct Is Used to Route, Protect, and Manage Wires Near Sensitive Electronic	
	Equipment and In Environments Where Heat Resistance or Public Safety Is A Concern. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 95°C (203°F). Halogen-Free, Polyphenylene Oxide (Ppo). Mounting Holes	
	Provided. 1.41" X 1.46" (35.8 MM X 37.1 MM) and 6.6' (2 M) Long. Cover Included. Color White. 5 Pieces Per Package.	
Weight per unit	1.5 (lbs/each)	
Product Category	Ducts, Raceways, Runways, Tray	
Features		
connection	DIN Standard Mounting Holes	
media	Yes	
Material, Color, and Finish		
Color	White	
Dimensions and Weight		
Length		
Size	1.46 x 1.41	
Width	1.46	
Descriptions		
Description	37MX37MMX2M WH WIRE DCT	
extra long description	PAN NNC37X37WH2 Panduct® NNC37X37WH	
Long Description	The NNC37X37WH2 Halogen-Free Wide Slot Wiring Duct is used to route, protect, and manage wires near sensitive electronic	
	equipment and in environments where heat resistance or public	
	safety is a concern. UL 94 flame class of V-0 with a UL recognized	
	continuous-use temperature up to 95°C (203°F). Halogen-Free,	
	Polyphenylene Oxide (PPO). Mounting holes provided. 1.41" x	
	1.46" (35.8 mm x 37.1 mm) and 6.6' (2 m) long. Cover included.	
	Color White. 5 pieces per package.	
Product Type	Panduct® NNC37X37WH2 Wide Slot Duct, White, Hal-Free Ppo, 1.	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manutac	turer	Intormat	ion
Brand	1		

Brand	PANDUIT
GTIN	00074983442775
Manufacturers Part Number	NNC37X37WH2
UPC	074983442775

Taxonomies, Classifications, and Categories Category Description Panduit & Wiremold Metallic & Non-Metallic Raceways

Weight Per meter 1.47

	Wiring Duct Base with Cover
Packaging	
Carton	1
Package	20

Uses, Certifications, and Standards

Application	NNC Wiring Duct is Used to Route, Protect, and Manage Wires
	near Sensitive Electronic Equipment and in Environments where
	Heat Resistance or Public Safety is a Concern
standard	CSA Approved; EN 45545-2 HL1; RoHS Compliant, UL Recognized,
	CE Compliant