

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Product Type

NPP16DEREFP Current-Monitoring Power/Relay Pack Lithonia Lighting - Acuity

Lithonia Lighting - Acuity		
Catalog Number	NPP16DEREFP	
Manufacturer	Lithonia Lighting - Acuity	
Description	The Nlight NPP16 Er Efp (External Fault Protection) Series Relay Pack Is Used to Switch Luminaires Powered Via An Emergency Circuit, Ideally Suited For Use In Conjunction With A Standard NNPP16 Efp Power/Relay Pack That Controls A Zone'S Normal Powered Lighting	
Weight per unit	0.7500 (lbs/each)	
Product Category	Lighting Accessories	
Features		
average life	Not Applicable	
dimmable	Yes	
Hardware	Yes	
Lamp Included	Not Applicable	
Material	Plastic	
Maximum Operating Temperature	60	
pallet quantity	100	
Voltage Rating	120,277	
Warranty	5	
Material, Color, and Finish		
Color	Red	
Finish	Gloss	
Dimensions and Weight		
Height	4	
Length	4	
Width	2.5	
Descriptions		
Description	CURRENT-MONITORING POWER/RELAY PACK	
extra long description	LITH NPP16 D ER EFP Power/Relay Pac	
Features	Design Select	
Long Description	The nLight nPP16 ER EFP (External Fault Protection) Series relay pack is used to switch luminaires powered via an emergency circuit, ideally suited for use in conjunction with a standard nnPP16 EFP power/relay pack that controls a zone's normal powered lighting	

Power Pack



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Nlight	
GTIN	00193047356824	
Manufacturers Part Number	NPP16 D ER EFP	
UPC	193047356824	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	POWER PACK
ckaging	

Packaging

99	
Carton	1
Weight	1
Weight Per each	0.75

Uses, Certifications, and Standards

Application	Education, Government, Healthcare, Hospitality, House of Worship, Manufacturing, Offices & Banks, Retail, Sports and Recreation, Warehouses
environmental conditions	Indoor
Mounting	Unit to J Box
standard	C-UL-US,ULCA Title 24,DLC Standard,ROHS