

Product Number: 74250

Order Abbreviation: PANELF1A/040UNVD840/24G/WH

General Description: Edge Lit Panel 1A, 40 Watts, 120-277V, 0-10V Dimmable, 80+ CRI, 4000K, 2x4, white finish



Product Information

| | |
|--|------------------------------------|
| Power Factor | ?0.90 |
| Primary Lamp Type | SMD |
| Minimum Operating Temperature - Celsius | -20 |
| Minimum Operating Temp - Fahrenheit | -4 |
| Total Harmonic Distortion (THD) | ?20 % |
| Efficacy (LPW) | 110 |
| Abbrev. With Packaging Info. | PANELF1A040UNVD84024GWH 3/CS 1/SKU |
| Color Temperature/CCT (K) | 4000 |
| Ordering Abbreviation | PANELF1A/040UNVD840/24G/WH |
| Average Rated Life 1 (hr) | 50000 |
| Lumens | 4200 |
| Nominal Voltage (V) | 120.00 |
| Nominal Wattage (W) | 40.00 |
| UPC Code | UPC046135742507 |
| Color Rendering Index (CRI) | >80 |
| Service Life Rating | ?50000 |
| Lumens (lm) | 4200 |
| Wattage (W) | 40.00 |
| Color Range | 4000 K |
| Connectors | Terminal block |
| Energy Star Rated | No |
| Fixture Warranty | 5 years |
| Housing | Aluminum |
| Luminaire Finish | White |
| Luminaire Type | Panel |
| Maximum Operating Temperature-Celsius | 40 |
| Maximum Operating Temperature-Fahrenheit | 104 |
| Power Input | 40 |
| Mounting | Recessed |
| Dimensions | 47.8x23.82x1.71 |
| Certification Listing | cETLus, FCC, RoHS, DLC |

Product Number: 74250

Order Abbreviation: PANELF1A/040UNVD840/24G/WH

General Description: Edge Lit Panel 1A, 40 Watts, 120-277V, 0-10V Dimmable, 80+ CRI, 4000K, 2x4, white finish



Product Information

| | |
|--|------------------------------------|
| Power Factor | ?0.90 |
| Primary Lamp Type | SMD |
| Minimum Operating Temperature - Celsius | -20 |
| Minimum Operating Temp - Fahrenheit | -4 |
| Total Harmonic Distortion (THD) | ?20 % |
| Efficacy (LPW) | 110 |
| Abbrev. With Packaging Info. | PANELF1A040UNVD84024GWH 3/CS 1/SKU |
| Color Temperature/CCT (K) | 4000 |
| Ordering Abbreviation | PANELF1A/040UNVD840/24G/WH |
| Average Rated Life 1 (hr) | 50000 |
| Lumens | 4200 |
| Nominal Voltage (V) | 120.00 |
| Nominal Wattage (W) | 40.00 |
| UPC Code | UPC046135742507 |
| Color Rendering Index (CRI) | >80 |
| Service Life Rating | ?50000 |
| Lumens (lm) | 4200 |
| Wattage (W) | 40.00 |
| Color Range | 4000 K |
| Connectors | Terminal block |
| Energy Star Rated | No |
| Fixture Warranty | 5 years |
| Housing | Aluminum |
| Luminaire Finish | White |
| Luminaire Type | Panel |
| Maximum Operating Temperature-Celsius | 40 |
| Maximum Operating Temperature-Fahrenheit | 104 |
| Power Input | 40 |
| Mounting | Recessed |
| Dimensions | 47.8x23.82x1.71 |
| Certification Listing | cETLus, FCC, RoHS, DLC |