


The TeleControl Series Technical Drawings



TeleControl Enclosures Dimensions

SIZE ID NUMBER	OVERALL H X W X D	INSIDE A X B X C	MOUNTING E X F	J	K	L	M	N	HOLE DIA.	SHIPPING WEIGHT	PANEL NUMBER
J1407TC	15.87 x 8.75 x 6.81 (403 x 222 x 173)	14.00 x 7.00 x 6.56 (356 x 178 x 167)	15 x 5 (381 x 127)	6.11 (155)	12.25 (311)	5.25 (133)	0.25 (6)	15.75 (400)	0.31 (8)	6.1 lbs.	BP1407*

Standard package does not include actual phone and installation of phone.

Other non-metallic enclosures available with phone window.

* Panel ordered separately.

The PolyStar Series

PC

PolyStar™ Enclosures are intended to be utilized for outdoor and indoor applications. The polycarbonate resin in the PolyStar™ Series received the best rating, an “F1” per UL 746C. This means that the resin has passed tests for UV exposure and water immersion. The PolyStar™ Series enclosures are rated 3R, 4, 4X, 12 per UL 50 and IP66 per IEC 60529. The material rating and the product rating can assure the user that the PolyStar™ Series enclosures are suitable for outdoor use and exposure.

PolyStar™ enclosures are manufactured with polycarbonate designed to perform in cold weather applications. In general, the product performance will not be adversely affected until temperatures below -40°F are realized. In our literature, we document a normal operating temperature of -20°F to +240°F (-20°C to +115°C). We do this to provide a safe operating range, as product application and enclosure placement are not always exactly known.

PolyStar Series Attributes

- Latches and hinges do not penetrate enclosure
- Easy to remove lid
- High performance inserts
- Integrated lock hasp
- Flush-fit side mount swing panel and DIN rail system
- Molded in bosses
- Multi-directional mounting feet
- Available in standard flat covers or domed covers as applicable on certain sizes

PolyStar Series Industry Standards

UL/cUL 50	File E342926 Type 3R, 4, 4X, 12
NEMA 250	Type 3R, 4, 4X, 12
IEC 60529	IP66
Temperature Range	(-20°F to +240°F) (-20°C to +115°C)
Flammability Rating	UL94-5VA/V0
Chemical Resistance	Full chemical resistance charts listed in appendix



PC

Technical Specifications - PolyStar™ Series

PC

Opaque Cover configuration - Hinged, 2 latches



PC Construction

Material	Polycarbonate with UV inhibitors
Gasket	Neoprene rope style
Recessed Screws	No protruding surfaces
Stainless Steel Hardware	300 Series stainless used on all hardware
Mounting Bosses	Panel mounting capability for fixed rear panel
Metal inserts	All threaded brass inserts accepting 10-32 screws
Side Mount Solutions	Variable height, any side mount capability

PC Industry Standards

UL/cUL 50	File E342926 Type 3R, 4, 4X, 12
NEMA 250	Type 3R, 4, 4X, 12
IEC 60529	IP66
Temperature Range	(-20°F to +240°F) (-20°C to +115°C)
Flammability Rating	UL94-5VA/V0
Chemical Resistance	Full chemical resistance charts listed in appendix

NOTES:

PC Accessories

Back Panels

Aluminum	BP__AL	pg. 149 - 150
Fiberglass	BP__FG	pg. 149 - 150
Stainless Steel	BP__SS	pg. 149 - 150
Carbon Steel	BP__CS	pg. 149 - 150

Swing Panel Kits (comes with mounts, screws, and panel)

Swing Panel Kit	PC_SPK	pg. 113
-----------------	--------	---------

Accessories

Slot Nut Kit (includes two nuts & two screws)	PCSNK	pg. 113
Swing Panel Mounts (4 per kit)	PCSPMK	pg. 113
Latch Kit (2 latches per kit) - replacement only	PCLATCHKIT	pg. 113
Accessory Kit (includes all screws, inserts, and mounting feet) - replacement only	PCACCESSORYKIT	pg. 113

PC Modifications

Custom Colors	pg. 12 - 13
Silk Screening	pg. 12 - 13
EMI/RFI Shielding	pg. 12 - 13
Custom Window	pg. 12 - 13
Custom Cutouts/Holes	pg. 12 - 13

CC

Technical Specifications - PolyStar™ Series

PC

Clear Cover configuration - Hinged, 2 latches



CC Construction

Material	Polycarbonate with UV inhibitors
Gasket	Neoprene rope style
Recessed Screws	No protruding surfaces
Stainless Steel Hardware	300 Series stainless used on all hardware
Mounting Bosses	Panel mounting capability for fixed rear panel
Metal inserts	All threaded brass inserts accepting 10-32 screws
Side Mount Solutions	Variable height, any side mount capability

CC Industry Standards

UL/cUL 50	File E342926 Type 3R, 4, 4X, 12
NEMA 250	Type 3R, 4, 4X, 12
IEC 60529	IP66
Temperature Range	(-20°F to +240°F) (-20°C to +115°C)
Flammability Rating	UL94-5VA/V0
Chemical Resistance	Full chemical resistance charts listed in appendix

NOTES:

CC Accessories

Back Panels

Aluminum	BP__AL	pg. 149 - 150
Fiberglass	BP__FG	pg. 149 - 150
Stainless Steel	BP__SS	pg. 149 - 150
Carbon Steel	BP__CS	pg. 149 - 150

Swing Panel Kits (comes with mounts, screws, and panel)

Swing Panel Kit	PC_SPK	pg. 113
-----------------	--------	---------


Accessories

Slot Nut Kit (includes two nuts & two screws)	PCSNK	pg. 113
Swing Panel Mounts (4 per kit)	PCSPMK	pg. 113
Latch Kit (2 latches per kit) - replacement only	PCLATCHKIT	pg. 113
Accessory Kit (includes all screws, inserts, and mounting feet) - replacement only	PCACCESSORYKIT	pg. 113

CC Modifications

Custom Colors	pg. 12 - 13
Silk Screening	pg. 12 - 13
EMI/RFI Shielding	pg. 12 - 13
Custom Window	pg. 12 - 13
Custom Cutouts/Holes	pg. 12 - 13

PolyStar™ Series Opaque Cover and Clear Cover Configuration Technical Drawings



PolyStar Series Enclosures - Opaque Cover and Clear Cover Configuration Dimensions


SIZE ID NUMBER	OVERALL H X W X D	INSIDE A X B X C	MOUNTING HOR. E X F	MOUNTING VER. E X F	MOUNTING 45 E X F	J	K	L	M	N	SHIPPING WEIGHT	PANEL NUMBER
PC606 PC606CC	7.41 x 8.68 x 5.84 (188 x 223 x 148)	5.94 x 5.94 x 5.02 (151 x 151 x 127)	3.64 x 8.40 (93 x 213)	8.04 x 3.64 (204 x 93)	6.75 x 6.74 (171 x 171)	4.50 (114)	4.25 (108)	4.25 (108)	8.89 (226)	8.89 (226)	2.50 lbs.	BP66*
PC806** PC806CC**	9.41 x 8.68 x 5.86 (239 x 223 x 149)	7.97 x 5.97 x 5.07 (202 x 152 x 129)	5.64 x 8.04 (143 x 213)	10.04 x 3.64 (255 x 93)	8.76 x 6.75 (223 x 171)	4.56 (116)	6.25 (159)	4.25 (108)	10.89 (277)	8.89 (226)	3.19 lbs.	BP86*
PC1008** PC1008CC**	11.41 x 10.68 x 6.36 (290 x 271 x 161)	9.96 x 7.96 x 5.57 (253 x 202 x 142)	7.64 x 10.04 (194 x 255)	12.04 x 5.64 (306 x 143)	10.76 x 8.75 (273 x 222)	5.05 (128)	8.25 (210)	6.25 (159)	12.89 (327)	10.89 (277)	4.31 lbs.	BP108*
PC1210** PC1210CC**	13.40 x 12.68 x 7.86 (340 x 322 x 200)	11.95 x 9.95 x 7.07 (304 x 253 x 180)	9.64 x 12.04 (245 x 306)	14.04 x 7.64 (357 x 194)	12.76 x 10.75 (324 x 273)	6.56 (167)	10.25 (260)	8.25 (210)	14.89 (378)	12.89 (327)	6.19 lbs.	BP1210*
PC1412** PC1412CC**	15.40 x 14.68 x 7.86 (391 x 373 x 200)	13.95 x 11.95 x 7.07 (354 x 304 x 180)	11.64 x 14.04 (296 x 357)	16.04 x 9.64 (407 x 245)	14.76 x 12.75 (375 x 324)	6.56 (167)	12.25 (311)	10.25 (260)	16.89 (429)	14.89 (378)	7.99 lbs.	BP1412*
PC1614** PC1614CC**	17.65 x 16.68 x 9.98 (448 x 424 x 253)	15.93 x 13.93 x 9.20 (405 x 354 x 234)	13.64 x 16.04 (347 x 407)	18.04 x 11.64 (458 x 296)	16.76 x 14.75 (426 x 375)	8.68 (220)	14.25 (362)	12.25 (311)	18.89 (480)	16.89 (429)	10.00 lbs.	BP1614*
PC1816 PC1816CC	19.41 x 18.68 x 11.90 (493 x 474 x 302)	17.83 x 15.83 x 11.08 (453 x 402 x 281)	15.64 x 18.04 (397 x 458)	20.04 x 13.64 (509 x 347)	18.75 x 16.74 (476 x 425)	10.56 (268)	16.25 (413)	14.25 (362)	20.89 (531)	18.89 (480)	11.25 lbs.	BP1816*

All measures are in inches, items in parentheses are in millimeters.

* Panel sold separately

** Domed covers available upon request, consult factory for details

The TeleControl Series Technical Drawings



TeleControl Enclosures Dimensions

SIZE ID NUMBER	OVERALL H X W X D	INSIDE A X B X C	MOUNTING E X F	J	K	L	M	N	HOLE DIA.	SHIPPING WEIGHT	PANEL NUMBER
J1407TC	15.87 x 8.75 x 6.81 (403 x 222 x 173)	14.00 x 7.00 x 6.56 (356 x 178 x 167)	15 x 5 (381 x 127)	6.11 (155)	12.25 (311)	5.25 (133)	0.25 (6)	15.75 (400)	0.31 (8)	6.1 lbs.	BP1407*

Standard package does not include actual phone and installation of phone.

Other non-metallic enclosures available with phone window.

* Panel ordered separately.

The PolyStar Series

PC

PolyStar™ Enclosures are intended to be utilized for outdoor and indoor applications. The polycarbonate resin in the PolyStar™ Series received the best rating, an “F1” per UL 746C. This means that the resin has passed tests for UV exposure and water immersion. The PolyStar™ Series enclosures are rated 3R, 4, 4X, 12 per UL 50 and IP66 per IEC 60529. The material rating and the product rating can assure the user that the PolyStar™ Series enclosures are suitable for outdoor use and exposure.

PolyStar™ enclosures are manufactured with polycarbonate designed to perform in cold weather applications. In general, the product performance will not be adversely affected until temperatures below -40°F are realized. In our literature, we document a normal operating temperature of -20°F to +240°F (-20°C to +115°C). We do this to provide a safe operating range, as product application and enclosure placement are not always exactly known.

PolyStar Series Attributes

- Latches and hinges do not penetrate enclosure
- Easy to remove lid
- High performance inserts
- Integrated lock hasp
- Flush-fit side mount swing panel and DIN rail system
- Molded in bosses
- Multi-directional mounting feet
- Available in standard flat covers or domed covers as applicable on certain sizes

PolyStar Series Industry Standards

UL/cUL 50	File E342926 Type 3R, 4, 4X, 12
NEMA 250	Type 3R, 4, 4X, 12
IEC 60529	IP66
Temperature Range	(-20°F to +240°F) (-20°C to +115°C)
Flammability Rating	UL94-5VA/V0
Chemical Resistance	Full chemical resistance charts listed in appendix



PC

Technical Specifications - PolyStar™ Series

PC

Opaque Cover configuration - Hinged, 2 latches



PC Construction

Material	Polycarbonate with UV inhibitors
Gasket	Neoprene rope style
Recessed Screws	No protruding surfaces
Stainless Steel Hardware	300 Series stainless used on all hardware
Mounting Bosses	Panel mounting capability for fixed rear panel
Metal inserts	All threaded brass inserts accepting 10-32 screws
Side Mount Solutions	Variable height, any side mount capability

PC Industry Standards

UL/cUL 50	File E342926 Type 3R, 4, 4X, 12
NEMA 250	Type 3R, 4, 4X, 12
IEC 60529	IP66
Temperature Range	(-20°F to +240°F) (-20°C to +115°C)
Flammability Rating	UL94-5VA/V0
Chemical Resistance	Full chemical resistance charts listed in appendix

NOTES:

PC Accessories

Back Panels

Aluminum	BP__AL	pg. 149 - 150
Fiberglass	BP__FG	pg. 149 - 150
Stainless Steel	BP__SS	pg. 149 - 150
Carbon Steel	BP__CS	pg. 149 - 150

Swing Panel Kits (comes with mounts, screws, and panel)

Swing Panel Kit	PC_SPK	pg. 113
-----------------	--------	---------

Accessories

Slot Nut Kit (includes two nuts & two screws)	PCSNK	pg. 113
Swing Panel Mounts (4 per kit)	PCSPMK	pg. 113
Latch Kit (2 latches per kit) - replacement only	PCLATCHKIT	pg. 113
Accessory Kit (includes all screws, inserts, and mounting feet) - replacement only	PCACCESSORYKIT	pg. 113

PC Modifications

Custom Colors	pg. 12 - 13
Silk Screening	pg. 12 - 13
EMI/RFI Shielding	pg. 12 - 13
Custom Window	pg. 12 - 13
Custom Cutouts/Holes	pg. 12 - 13

CC

Technical Specifications - PolyStar™ Series

PC

Clear Cover configuration - Hinged, 2 latches



CC Construction

Material	Polycarbonate with UV inhibitors
Gasket	Neoprene rope style
Recessed Screws	No protruding surfaces
Stainless Steel Hardware	300 Series stainless used on all hardware
Mounting Bosses	Panel mounting capability for fixed rear panel
Metal inserts	All threaded brass inserts accepting 10-32 screws
Side Mount Solutions	Variable height, any side mount capability

CC Industry Standards

UL/cUL 50	File E342926 Type 3R, 4, 4X, 12
NEMA 250	Type 3R, 4, 4X, 12
IEC 60529	IP66
Temperature Range	(-20°F to +240°F) (-20°C to +115°C)
Flammability Rating	UL94-5VA/V0
Chemical Resistance	Full chemical resistance charts listed in appendix

NOTES:

CC Accessories

Back Panels

Aluminum	BP__AL	pg. 149 - 150
Fiberglass	BP__FG	pg. 149 - 150
Stainless Steel	BP__SS	pg. 149 - 150
Carbon Steel	BP__CS	pg. 149 - 150

Swing Panel Kits (comes with mounts, screws, and panel)

Swing Panel Kit	PC_SPK	pg. 113
-----------------	--------	---------


Accessories

Slot Nut Kit (includes two nuts & two screws)	PCSNK	pg. 113
Swing Panel Mounts (4 per kit)	PCSPMK	pg. 113
Latch Kit (2 latches per kit) - replacement only	PCLATCHKIT	pg. 113
Accessory Kit (includes all screws, inserts, and mounting feet) - replacement only	PCACCESSORYKIT	pg. 113

CC Modifications

Custom Colors	pg. 12 - 13
Silk Screening	pg. 12 - 13
EMI/RFI Shielding	pg. 12 - 13
Custom Window	pg. 12 - 13
Custom Cutouts/Holes	pg. 12 - 13

PolyStar™ Series Opaque Cover and Clear Cover Configuration Technical Drawings



PolyStar Series Enclosures - Opaque Cover and Clear Cover Configuration Dimensions

SIZE ID NUMBER	OVERALL H X W X D	INSIDE A X B X C	MOUNTING HOR. E X F	MOUNTING VER. E X F	MOUNTING 45 E X F	J	K	L	M	N	SHIPPING WEIGHT	PANEL NUMBER
PC606 PC606CC	7.41 x 8.68 x 5.84 (188 x 223 x 148)	5.94 x 5.94 x 5.02 (151 x 151 x 127)	3.64 x 8.40 (93 x 213)	8.04 x 3.64 (204 x 93)	6.75 x 6.74 (171 x 171)	4.50 (114)	4.25 (108)	4.25 (108)	8.89 (226)	8.89 (226)	2.50 lbs.	BP66*
PC806** PC806CC**	9.41 x 8.68 x 5.86 (239 x 223 x 149)	7.97 x 5.97 x 5.07 (202 x 152 x 129)	5.64 x 8.04 (143 x 213)	10.04 x 3.64 (255 x 93)	8.76 x 6.75 (223 x 171)	4.56 (116)	6.25 (159)	4.25 (108)	10.89 (277)	8.89 (226)	3.19 lbs.	BP86*
PC1008** PC1008CC**	11.41 x 10.68 x 6.36 (290 x 271 x 161)	9.96 x 7.96 x 5.57 (253 x 202 x 142)	7.64 x 10.04 (194 x 255)	12.04 x 5.64 (306 x 143)	10.76 x 8.75 (273 x 222)	5.05 (128)	8.25 (210)	6.25 (159)	12.89 (327)	10.89 (277)	4.31 lbs.	BP108*
PC1210** PC1210CC**	13.40 x 12.68 x 7.86 (340 x 322 x 200)	11.95 x 9.95 x 7.07 (304 x 253 x 180)	9.64 x 12.04 (245 x 306)	14.04 x 7.64 (357 x 194)	12.76 x 10.75 (324 x 273)	6.56 (167)	10.25 (260)	8.25 (210)	14.89 (378)	12.89 (327)	6.19 lbs.	BP1210*
PC1412** PC1412CC**	15.40 x 14.68 x 7.86 (391 x 373 x 200)	13.95 x 11.95 x 7.07 (354 x 304 x 180)	11.64 x 14.04 (296 x 357)	16.04 x 9.64 (407 x 245)	14.76 x 12.75 (375 x 324)	6.56 (167)	12.25 (311)	10.25 (260)	16.89 (429)	14.89 (378)	7.99 lbs.	BP1412*
PC1614** PC1614CC**	17.65 x 16.68 x 9.98 (448 x 424 x 253)	15.93 x 13.93 x 9.20 (405 x 354 x 234)	13.64 x 16.04 (347 x 407)	18.04 x 11.64 (458 x 296)	16.76 x 14.75 (426 x 375)	8.68 (220)	14.25 (362)	12.25 (311)	18.89 (480)	16.89 (429)	10.00 lbs.	BP1614*
PC1816 PC1816CC	19.41 x 18.68 x 11.90 (493 x 474 x 302)	17.83 x 15.83 x 11.08 (453 x 402 x 281)	15.64 x 18.04 (397 x 458)	20.04 x 13.64 (509 x 347)	18.75 x 16.74 (476 x 425)	10.56 (268)	16.25 (413)	14.25 (362)	20.89 (531)	18.89 (480)	11.25 lbs.	BP1816*

All measures are in inches, items in parentheses are in millimeters.

* Panel sold separately

** Domed covers available upon request, consult factory for details