

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**UPC** 

## **PDREPWH Caseta Repeater** *Lutron*

Soon	
Catalog Number	PDREPWH
Manufacturer	Lutron
Description	Lutron Coasta Creart Wireless Departer/Dangs Extender White
Weight per unit	·
Product Category	Line Construction Material
Features	
Material	Plastic
media	Yes
Voltage Rating	5
Material, Color, and Finish	
Color	White
Finish	Gloss
Dimensions and Weight	
Height	1.19
Length	2.75
Width	2.75
Descriptions	
Description	CASETA REPEATER
extra long description	LUT PD-REP-WH Cas ta Repeater/Range
Features	With the Caseta Smart Wireless Repeater by Lutron, you can now
	extend the range of your Caseta system up to 60 ft. Use the
	included power adapter to plug the repeater into an outlet
	within 60 ft. of your Caseta smart hub in room where coverage
	can be problematic - no extra ethernet connection required. This
	is ideal for homes that need extra range due to unique layouts,
	smart hubs that are not centrally located, or dense, concrete, or
Long Description	cement walls.  Lutron Caseta Smart Wireless Repeater/Range Extender, White
Long Description Product Type	
Product Type Special Features	Cas Ta Repeater/Range Extender Expands RF range. Easily adds to an existing system through the
Special Features	Caséta App1 or system software . Can add one wireless repeater
	per system. Works with Caséta Wireless systems only
Manufacturer Information	
Brand	Lutron
GTIN	00784276274043
Manufacturers Part Number	PD-REP-WH
and the second s	

784276274043



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	Pack	a	gı	n	g
-----------	------	---	----	---	---

Carton	1	
Package	12	
Weight Per each	0.43	

## Uses, Certifications, and Standards

Application	Lighting and shade Control
Enclosure	Plastic
Frequency Rating	431 to 437
Mounting	Tabletop
standard	cULus Listed FCC approved IC certified IFETEL certified
Temperature Rating	32 to 104