



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## PLG150S 1-1/2" Square Head Plug *Appleton/Oz Gedney*

Catalog Number	PLG150S
Manufacturer	Appleton/Oz Gedney
Description	Unilets Square Head Close-Up Plug, Size: 1-1/2 In, Material: Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered MNPT, Standard: UI 886 (1203), UI File Number E10444, Csa C22.2 No. 25 and 30, Csa 065181, UI Listed For Class I,
Weight per unit	0.4700 (lbs/each)
Product Category	Bar Hangers & Outlet Box Accy.

### Features

connection	Tapered MNPT
Material	Malleable Iron

### Material, Color, and Finish

Finish	Zinc Electroplate
--------	-------------------

### Dimensions and Weight

Size	1-1/2
------	-------

### Descriptions

Description	1-1/2" SQUARE HEAD PLUG
extra long description	APP PLG-150S PLUG 1-1/2 SQR HEAD C
Long Description	UNILETS Square Head Close-Up Plug, Size: 1-1/2 IN, Material: Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered MNPT, Standard: UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I,
Product Type	Plug 1-1/2 SQR Head Close-Up
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity; Explosionproof, dust-ignitionproof; Smooth, rounded integral bushing in each hub protects conductor insulation

### Manufacturer Information

Brand	Appleton
GTIN	00781381652308
Manufacturers Part Number	PLG-150S
UPC	781381652308

### Taxonomies, Classifications, and Categories

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs
Type	Square Head Close-Up Plug



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	10
Package	100
Weight Per each	0.47

## Uses, Certifications, and Standards

Application	For Use With Threaded Rigid Metal Conduit and IMC
standard	And Class III;Class II, Groups E, F, G;UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Groups B, C, D