

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **PLT3SM 11.5" 50LB WHT CBL Tie** Panduit Corporation

Catalon Niverbor	DLT2CM
Catalog Number	PLT3SM  Panduit Corneration
Manufacturer Description	Panduit Corporation Panduit PLT3S-M Locking Cable Ties Are Designed to Satisfy The Needs Of General Applications, While Delivering Consistent Performance and Reliability. Featuring A Curved Tip to Allow For Easy Pick Up From Flat Surfaces and Faster Initial Threading. Standard Cross Section, 11.5" (292MM) Length. For Indoor Use, Made Of Nylon 6.6, Are Natural In Color and Come In Packages Of 1000.
Weight per unit	0.0051 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
media	Yes
Tensile Strength	50
<b>Dimensions and Weight</b>	
Length	11.5
Thickness	0.06
Descriptions	
Description	11.5" 50LB WHT CBL TIE
extra long description	PAN PLT3S-M Pan-Ty® PLT3S-M Cable T
Long Description	Panduit PLT3S-M Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent
	performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading.
	Standard cross section, 11.5" (292mm) length. For indoor use, made of Nylon 6.6, are natural in color and come in packages of 1000.
Product Type	Pan-Ty® PLT3S-M Cable Tie, PA6.6, 11.5"L, 50LB, PK1000
Special Features	Indoor
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983540617
Manufacturers Part Number	PLT3S-M
UPC	074983540617
Taxonomies, Classifications, and (	Categories
Туре	December 2016 La The



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pac	kaa	ina
	J	<b>J</b>

Carton	1000	
Package	2000	
Weight Per each	0.005144	

## Uses, Certifications, and Standards

standard	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant
	(Type 2S, 21S), RoHS Compliant