

# Grounding Bushings and Split Couplings

## Grounding Bushings

### Description:

Plasti-Bond REDH<sub>2</sub>OT grounding bushings are used on threaded PVC-coated rigid conduit to provide a means of grounding conduit through an insulated bushing.

### Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 10 trade sizes from 1/2" through 4"
- Aluminum lug for copper or aluminum grounding conductor



### GROUNDING BUSHINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2"      | PBGLL1            | 0.1            |
| 3/4"      | PBGLL2            | 0.1            |
| 1"        | PBGLL3            | 0.1            |
| 1-1/4"    | PBGLL4            | 0.2            |
| 1-1/2"    | PBGLL5            | 0.2            |
| 2"        | PBGLL6            | 0.3            |
| 2-1/2"    | PBGLL7            | 0.5            |
| 3"        | PBGLL8            | 0.7            |
| 3-1/2"    | PBGLL9            | 1.0            |
| 4"        | PBGLL10           | 1.1            |

## Split Couplings

### Description:

Plasti-Bond REDH<sub>2</sub>OT split couplings are used to connect two pieces of conduit where the conduit can't be turned because of limited clearance between runs or a wall or other obstruction.

### Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings



### SPLIT COUPLINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2"      | PRSSP50           | 0.2            |
| 3/4"      | PRSSP75           | 0.3            |
| 1"        | PRSSP100          | 0.4            |
| 1-1/4"    | PRSSP125          | 0.6            |
| 1-1/2"    | PRSSP150          | 0.7            |
| 2"        | PRSSP200          | 1.0            |
| 2-1/2"    | PRSSP250          | 2.3            |
| 3"        | PRSSP300          | 3.0            |
| 3-1/2"    | PRSSP350          | 3.8            |
| 4"        | PRSSP400          | 4.1            |
| 5"        | PRSSP500          | 6.0            |
| 6"        | PRSSP600          | 8.6            |

# Grounding Bushings and Split Couplings

## Grounding Bushings

### Description:

Plasti-Bond REDH<sub>2</sub>OT grounding bushings are used on threaded PVC-coated rigid conduit to provide a means of grounding conduit through an insulated bushing.

### Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 10 trade sizes from 1/2" through 4"
- Aluminum lug for copper or aluminum grounding conductor



### GROUNDING BUSHINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2"      | PBGLL1            | 0.1            |
| 3/4"      | PBGLL2            | 0.1            |
| 1"        | PBGLL3            | 0.1            |
| 1-1/4"    | PBGLL4            | 0.2            |
| 1-1/2"    | PBGLL5            | 0.2            |
| 2"        | PBGLL6            | 0.3            |
| 2-1/2"    | PBGLL7            | 0.5            |
| 3"        | PBGLL8            | 0.7            |
| 3-1/2"    | PBGLL9            | 1.0            |
| 4"        | PBGLL10           | 1.1            |

## Split Couplings

### Description:

Plasti-Bond REDH<sub>2</sub>OT split couplings are used to connect two pieces of conduit where the conduit can't be turned because of limited clearance between runs or a wall or other obstruction.

### Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings



### SPLIT COUPLINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2"      | PRSSP50           | 0.2            |
| 3/4"      | PRSSP75           | 0.3            |
| 1"        | PRSSP100          | 0.4            |
| 1-1/4"    | PRSSP125          | 0.6            |
| 1-1/2"    | PRSSP150          | 0.7            |
| 2"        | PRSSP200          | 1.0            |
| 2-1/2"    | PRSSP250          | 2.3            |
| 3"        | PRSSP300          | 3.0            |
| 3-1/2"    | PRSSP350          | 3.8            |
| 4"        | PRSSP400          | 4.1            |
| 5"        | PRSSP500          | 6.0            |
| 6"        | PRSSP600          | 8.6            |