

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	egree 6" PT CNTR Solid grand
Catalog Number	
Manufacturer	Pass & Seymour/Legrand
Description	Plugtail Registered Connectors, Right Angle, Solid, 6-Inch Plugtail Registered Devices and Connectors Mean That Device Installation Is The Same Regardless Of Skill Level Of The Installer. The UI-Listed Connectors Are Keyed to Ensure Proper Wiring Installation Into Each Receptacle.
Weight per unit	0.0682 (lbs/each)
Product Category	Outlets, Jacks, & Plates
Features	
Dielectric Strength	Withstands 2000V minimum
media	Mark
Number of Wires	2
Poles	
Wattage	Electrical power is expressed in Amps and Volts.
Wire Size	12 AWG
Material, Color, and Finish	
Color	White
Finish	Matte
Dimensions and Weight	
Size	7.5
Descriptions	
Description	90 DEGREE 6" PT CNTR SOLID
extra long description	P&S PTRA6SOL 90 DEGREE 6 IN PT CNTR
Long Description	PlugTail Registered Connectors, Right Angle, Solid, 6-inch PlugTail Registered devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.
Product Type	90 Degree 6 In PT CNTR Solid
Special Features	Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing. Large brass contacts snugly terminate on device blade terminals. Pre-stripped connector leads fasten to conductors, easier than standard pigtails. Exclusive patented feature, circuit label on back allows permanent circuit identification.



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007044553
Manufacturers Part Number	PTRA6-SOL
UPC	785007044553
Taxonomies, Classifications, and C	ategories
Category Description	Miscellaneous residential devices
Туре	PlugTail™ Connector - Right Angle
Packaging	
Carton	
Package	250
Weight Per each	0.0682
Uses, Certifications, and Standard	S
Application	Commercial
environmental conditions	Flammability: UL94 V2
Mounting	Device, Wall
standard	CULUS, UL, cULus UL498
Temperature Rating	-40° - 60° C