

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### PTRA6STR 90 Degree 6" PT Conn Pass & Seymour/Legrand

Catalog Number	PTRA6STR
Manufacturer	Pass & Seymour/Legrand
Description	Plugtail® Connectors, Right Angle, Stranded, 6-Inch Plugtail®
•	Devices and Connectors Mean That Device Installation Is The
	Same Regardless Of Skill Level Of The Installer. The UI-Listed
	Connectors Are Keyed to Ensure Proper Wiring Installation Into
	Each Receptacle.
Weight per unit	0.0687 (lbs/each)
Product Category	Outlets, Jacks, & Plates

#### **Features**

Dielectric Strength	Withstands 2000V minimum
media	Yes
Number of Wires	3
Poles	2
Wattage	Electrical power is expressed in Amps and Volts.
Wire Size	12 AWG

#### Material, Color, and Finish

Color	White
Finish	Matte

#### **Dimensions and Weight**

<b>J</b>	
Size 7.5	

#### **Descriptions**

on iptions	
Description	90 DEGREE 6" PT CONN
extra long description	P&S PTRA6STR 90 DEGREE 6 IN PT CONN
Long Description	PlugTail® Connectors, Right Angle, Stranded, 6-inch PlugTail® devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.
Product Type	90 Degree 6 In PT Connector
Special Features	Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing. Large brass contacts snugly terminate on device blade terminals. Pre-stripped connector leads fasten to conductors, easier than standard pigtails. Exclusive patented feature, circuit label on back allows permanent circuit identification.



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Ν	Л	an	uf	act	tur	er	Inf	orr	ma	tior	1
---	---	----	----	-----	-----	----	-----	-----	----	------	---

Brand	Pass and Seymour	
GTIN	00785007044546	
Manufacturers Part Number	PTRA6-STR	
UPC	785007044546	

#### **Taxonomies, Classifications, and Categories**

Category Description	Commercial receptacles
Type	PlugTail™ Connector - Right Angle

#### Packaging

···-g···g		
Carton	1	
Package	250	
Weight Per each	0.0687	

#### Uses, Certifications, and Standards

Application Commercial	
environmental conditions Flammability: UL94 V2	
Mounting Device, Wall	
standard CULUS, UL, cULus UL498	
Temperature Rating -40° - 60° C	