



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **RB200100A Reducing Bushing, Size: 2 X 1 In, Material: Alumin** *Appleton/Oz Gedney*

Catalog Number	RB200100A
Manufacturer	Appleton/Oz Gedney
Description	Reducing Bushing, Size: 2 X 1 In, Material: Aluminum, Finish: Natural, Connection: NPT, Standard: Class I: Groups A, B, C, D, Class Ii: Groups E, F, G, Class Iii, UI 886 (1203), UI E10444, Csa C22.2 No. 25, C22.2 No. 30, Csa 065181, Fo
Weight per unit	0.0100 (lbs/each)
Product Category	Aluminum

### **Features**

connection	NPT
Material	Aluminum

### **Material, Color, and Finish**

Finish	Unfinished
--------	------------

### **Dimensions and Weight**

Size	2 X 1
------	-------

### **Descriptions**

Description	REDUCING BUSHING, SIZE: 2 X 1 IN, MATERIAL: ALUMIN
extra long description	APP RB200-100A RDC BUSH ALUM 2 TO 1
Long Description	Reducing Bushing, Size: 2 X 1 IN, Material: Aluminum, Finish: Natural, Connection: NPT, Standard: Class I: Groups A, B, C, D, Class II: Groups E, F, G, Class III, UL 886 (1203), UL E10444, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181, Fo
Product Type	RDC Bush Alum 2 to 1 In NPT
Special Features	Smooth rounded integral bushing protects conductor insulation

### **Manufacturer Information**

Brand	Appleton
GTIN	00781381322126
Manufacturers Part Number	RB200-100A
UPC	781381322126

### **Taxonomies, Classifications, and Categories**

Category Description	PVC SPACERS
Type	Reducing Bushing

### **Packaging**

Carton	5
Package	25
Weight Per each	0.01



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

For Reducing Conduit Entries To A Smaller Size In Threaded Rigid  
And IMC Conduit Systems

standard

Class I: Groups A, B, C, D, Class II: Groups E, F, G, Class III, UL 886  
(1203), UL E10444, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181