



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



RB2TZ 3/4"X1/2" Red Bush- Steel

Topaz - Southwire LLC

Catalog Number	RB2TZ
Manufacturer	Topaz - Southwire LLC
Description	Rigid Conduit Reducing Bushing, Threaded Type; Steel Material; 0.92 Inch Dia X 0.65 Inch L Size; Imc/Rigid Conduit Used On; 1/2 Inch Small End Trade Size; 3/4 Inch Large End Trade Size; 100 Per Case Standard Package
Weight per unit	N/A
Product Category	Rigid Conduit Fittings - Steel

Features

Material	Steel
----------	-------

Dimensions and Weight

Size	0.92 Inch Dia x 0.65 Inch L
------	-----------------------------

Descriptions

Commodity Description	Rigid Conduit Fittings - Steel
Description	3/4"X1/2" RED BUSH- STEEL
extra long description	ROUND, THREADED TYPE; ZINC PLATED STEEL MATERIAL; 0.92 INCH DIAMETER X 0.65 INCH LENGTH SIZE; IMC/RIGID CONDUIT USED ON; 1/2 INCH SMALL END TRADE SIZE; 3/4 INCH LARGE END TRADE SIZE; 100 PER CASE STANDARD PACKAGE; APPLICATION DRY LOCATION AND TO REDUCE THE ENTRY SIZE OF A RUN OF THREADED CONDUIT
Long Description	RIGID CONDUIT REDUCING BUSHING, THREADED TYPE; STEEL MATERIAL; 0.92 INCH DIA X 0.65 INCH L SIZE; IMC/RIGID CONDUIT USED ON; 1/2 INCH SMALL END TRADE SIZE; 3/4 INCH LARGE END TRADE SIZE; 100 PER CASE STANDARD PACKAGE
Product Type	Rigid Conduit Reducing Bushing

Manufacturer Information

Brand	SOUTHWIRE ROUGH ELECTRICAL COMPONENTS
GTIN	00751338200708
Manufacturers Part Number	RB2TZ
UPC	751338200708

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	THREADED



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Trade Size

Large End Trade Size 3/4 INCH

Small End Trade Size 1/2 INCH

Packaging

Carton 1

Package 100

Standard Package 100 PER CASE

Weight Per each 0

Uses, Certifications, and Standards

Used On IMC/RIGID CONDUIT