



Temporary Power Centers with GFCI Protection

50A Input
20A, 30A, 50A Output
120/240V/AC (Max.)


Temporary Power Centers

RhinoBox NEMA 3R



RB300M

Rating A	V/AC	Distribution Devices	Receptacle Rating	Protection Overload	GFCI	Catalog No.*	
50 (Max.)	120/240	(6) WR Duplex Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB300M	•
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(6) Single Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB301M	•
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(6) Locking Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB302M	•
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(3) Single Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB303M	•
		(3) Locking Receptacles	20A, 125V	✓	✓		
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(7) WR Duplex Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB3001M	•
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(7) Locking Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB3021M	•
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		



*Automatic GFCI reset configurations are available. When ordering automatic GFCI reset RhinoBox replace "M" in Catalog No. with "A". Example: RB300A = Automatic; RB300M = Manual.

NEMA 1 configurations are available. To order, replace "3" in Catalog No. with "2" for NEMA 1 enclosure. Example: RB300M = NEMA 3R; RB200M = NEMA 1.

Specification Information:

RhinoBox: L-11

Icon Key

NAFTA Compliant - see page O-30

RhinoBox™ Temporary Power Centers

50A Input
20A, 30A, 50A Output
120/240V/AC (Max.)

	Device Type	NEMA 1 Enclosures RB200 Series, Automatic or Manual Reset	NEMA 3R Enclosures RB300 Series, Automatic or Manual Reset
	Input	50A, 120/240V/AC, 60Hz, 3-Pole, 4-Wire Grounding	50A, 120/240V/AC, 60Hz, 3-Pole, 4-Wire Grounding
	Testing & Code Compliance	<ul style="list-style-type: none"> • cETLus Listed for indoor use 	<ul style="list-style-type: none"> • cETLus Listed for indoor or outdoor use
		<ul style="list-style-type: none"> • Complies with NEC Articles 525 & 590 	<ul style="list-style-type: none"> • Complies with NEC Articles 525 & 590
		<ul style="list-style-type: none"> • Complies with OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements 	<ul style="list-style-type: none"> • Complies with OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements
		<ul style="list-style-type: none"> • Conforms to UL 1640 and CSA C22.2, no. 14 	<ul style="list-style-type: none"> • Conforms to UL 1640 and CSA C22.2, no. 14
Specifications: Environmental	Enclosure Type	NEMA 1	NEMA 3R
Specifications: Electrical	GFCI Protection for 20A Receptacles	Yes	Yes
	Overload Protection	Yes	Yes
Materials:	Enclosure	Cold-rolled 18 gauge steel	Cold-rolled 18 gauge steel
	Legs	Cold-rolled 10 gauge steel	Cold-rolled 10 gauge steel



Temporary Power Centers with GFCI Protection

50A Input
20A, 30A, 50A Output
120/240V/AC (Max.)


Temporary Power Centers

RhinoBox NEMA 3R



RB300M

Rating A	V/AC	Distribution Devices	Receptacle Rating	Protection Overload	GFCI	Catalog No.*	
50 (Max.)	120/240	(6) WR Duplex Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB300M	•
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(6) Single Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB301M	•
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(6) Locking Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB302M	•
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(3) Single Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB303M	•
		(3) Locking Receptacles	20A, 125V	✓	✓		
		(1) Locking Receptacle	30A, 250V	✓	-		
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(7) WR Duplex Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB3001M	•
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		
50 (Max.)	120/240	(7) Locking Receptacles	20A, 125V	✓	✓	<input type="checkbox"/> RB3021M	•
		(1) Locking Inlet	50A, 125/250V	-	-		
		(1) Locking Outlet	50A, 125/250V	-	-		



*Automatic GFCI reset configurations are available. When ordering automatic GFCI reset RhinoBox replace "M" in Catalog No. with "A". Example: RB300A = Automatic; RB300M = Manual.

NEMA 1 configurations are available. To order, replace "3" in Catalog No. with "2" for NEMA 1 enclosure. Example: RB300M = NEMA 3R; RB200M = NEMA 1.

Specification Information:

RhinoBox: L-11

Icon Key

NAFTA Compliant - see page O-30

RhinoBox™ Temporary Power Centers

50A Input
20A, 30A, 50A Output
120/240V/AC (Max.)

	Device Type	NEMA 1 Enclosures RB200 Series, Automatic or Manual Reset	NEMA 3R Enclosures RB300 Series, Automatic or Manual Reset
	Input	50A, 120/240V/AC, 60Hz, 3-Pole, 4-Wire Grounding	50A, 120/240V/AC, 60Hz, 3-Pole, 4-Wire Grounding
	Testing & Code Compliance	<ul style="list-style-type: none"> • cETLus Listed for indoor use 	<ul style="list-style-type: none"> • cETLus Listed for indoor or outdoor use
		<ul style="list-style-type: none"> • Complies with NEC Articles 525 & 590 	<ul style="list-style-type: none"> • Complies with NEC Articles 525 & 590
		<ul style="list-style-type: none"> • Complies with OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements 	<ul style="list-style-type: none"> • Complies with OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements
		<ul style="list-style-type: none"> • Conforms to UL 1640 and CSA C22.2, no. 14 	<ul style="list-style-type: none"> • Conforms to UL 1640 and CSA C22.2, no. 14
Specifications: Environmental	Enclosure Type	NEMA 1	NEMA 3R
Specifications: Electrical	GFCI Protection for 20A Receptacles	Yes	Yes
	Overload Protection	Yes	Yes
Materials:	Enclosure	Cold-rolled 18 gauge steel	Cold-rolled 18 gauge steel
	Legs	Cold-rolled 10 gauge steel	Cold-rolled 10 gauge steel