Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685



RB6T8 FBAY 6LMP T8 32W

RAB LIGHTING

Catalog Number	RB6T8
Manufacturer	RAB LIGHTING
Description	RAB RBAY 6 X 32W T8 LINEAR FL HIGH BAY WITH Y HOOK WHITE
Weight per unit	19.9 (lbs/each)
Product Category	Fluorescent Highbay Lighting

Features

Lamp Type	T8
Voltage Rating	ELBOW FITTING, 316 STAINLESS STEEL MATERIAL; 1/2 INCH SIZE A; 1/2 INCH SIZE B; .5 SIZE A - DECIMAL; .5 SIZE B - DECIMAL; 1/2 SIZE A - FRACTIONAL; 1/2 SIZE B - FRACTIONAL; NUCLEAR, PHARMACEUTICAL INDUSTRY CHEMICAL, PETROCHEMICAL APPLICATION; CAST PROCESS
Wattage	Mini
Lumens	3.05k lm

Descriptions

Description	FBAY 6LMP T8 32W
Long Description	RAB RBAY 6 X 32W T8 LINEAR FL HIGH BAY WITH Y HOOK WHITE
Product Type	Rab Rbay 6 X 32W T8 Linear FL High Bay W
Special Features	Zinc Plated Cold Rolled Steel
Extra Long Description	RAB RB6T8 RAB RBAY 6 X 32W T8 LINEA

Manufacturer Information

Brand	Rab Lighting
GTIN	00019813018508
Manufacturers Part Number	RB6T8
UPC	885360

Taxonomies, Classifications, and Categories

Category Description	Fluorescent Fixtures & Accessories
Type	CEILING

Packaging

Carton	1
Weight Per Each	19.9 (lbs/each)

RB6T8

RAB offers energy efficient fluorescent fixtures for large space lighting including warehouses, factories, and distribution centers. The RBAY delivers the high quality needed for these applications with strong, heavy duty 22 gauge rigid housing with no sharp edges. The superior strong-box protective foam case packaging protects the RBAY so it arrives in perfect shape and ready to install.

Color: N/A

Weight: 21.0 lbs





Lamp Info

Type:	T8
Watts:	192W
Shape/Size:	N/A
Base:	N/A
ANSI:	N/A
Hours:	24,000
Lamp Lumens:	10,784
Efficacy:	62 LPW

Ballast Info

Type:	Instant Start
120V:	1.45A
208V:	N/A
240V:	N/A
277V:	0.61A
Input Watts:	173W
Efficiency:	111%

Technical Specifications

UL Listing:
Dry Locations Only. Ceiling Mount Only.

Housing:
Heavy duty 22 gauge steel housing and wiring box with 1/2" NPS knockouts. Painted white. Easy wiring and maintenance access panel. Includes "Y" hooks.

Reflector:
Alanod 320G-E with reflectivity of ≥86%.

Lamp:
T8 Linear (not supplied).

Ballast:
Instant Start, Universal Voltage 120 - 277V (not suitable for use with occupancy sensors).

Ballast Minimum Starting Temperature:
0°F.

CRI:
85.

Total Watts:
6x32W.

Input Volts:
120-277V.

Input Amps:
1.49/.65.

Ballast Factor:
0.88.

Base:
Medium Bi Pin.

Mounts:
Surface or Chain (Y Hooks included).

Patents:
RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Copyright ©2013 RAB Lighting, Inc. All Rights Reserved