

# Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### **RE63SA 2X1 Alu Reducing Bushing** Crouse-Hinds

Catalog Number	RE63SA		
Manufacturer	Crouse-Hinds		
Description	Eaton Crouse-Hinds Series Re Reducer, Rigid/Imc, End 1: 2" NPT, End 2: 1" NPT, Copper-Free Aluminum		
Weight per unit	0.3100 (lbs/each)		
Product Category	Aluminum		
eatures			
connection	Threaded		
dimensions	2.3800 IN X 1.0600 IN X 2.3800 IN		
Material	Copper-Free Aluminum		
Descriptions			
Description	2X1 ALU REDUCING BUSHING		
extra long description	CRS-H RE63 SA 2 TO 1 AL REDUCING BU		
Features	Crouse-Hinds series RE, REA and REC explosionproof reducers an used in rigid/IMC conduit systems to reduce conduit hubs to a smaller size (RE), connect two different sizes of conduit together (REC), or enlarge drilled and tapped openings by one NPT size (REA). PLG explosionproof plugs are used for closing threaded conduit hubs.		
Long Description	Eaton Crouse-Hinds series RE reducer, Rigid/IMC, End 1: 2" NPT, End 2: 1" NPT, Copper-free aluminum		
Product Type	2 to 1 Al Reducing Bush		
Special Features	Reducing fitting		
Manufacturer Information			
Brand	Eaton		
GTIN	00782274746968		
Manufacturers Part Number	RE63 SA		
UPC	782274746968		
Faxonomies, Classifications, and	Categories		
Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs		
Туре	REDUCER		
<b>-</b> 1			

### Packaging

craying		
Carton	1	
Package	10	
Weight Per each	0.31	



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

#### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other	
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II	
	Div 2 Group F G, Class III	
standard	UL 886, CSA C22.2	