



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## RSCND304150 1-1/2" 304SS Conduit 10'

*Robroy/Stainless Steel*

Catalog Number	RSCND304150
Manufacturer	Robroy/Stainless Steel
Description	Robroy Stainless Rigid Conduit Is Designed to Provide Protection For Wiring and Cable In Electrical Systems and Withstand Harsh Corrosive Environments. Conduit Is Available In 304 or 316 and Polished to A Bright Finish Allowing For A Surface That Requires Minimal Cleaning and Meets Sanitary Requirements. Each 10' Length Of Conduit Is Threaded At Both Ends and Supplied With One Coupling.
Weight per unit	277.0 (lbs/each)
Product Category	Flexible Metallic Conduit

### Features

fitting type	Conduit
Material	304

### Material, Color, and Finish

Finish	Brushed
--------	---------

### Dimensions and Weight

Length	10
Width	1.9

### Descriptions

Description	1-1/2" 304SS CONDUIT 10'
extra long description	ROB-R CND304-150 COND 1-1/2" 304
Long Description	Robroy Stainless Rigid Conduit is designed to provide protection for wiring and cable in electrical systems and withstand harsh corrosive environments. Conduit is available in 304 or 316 and polished to a bright finish allowing for a surface that requires minimal cleaning and meets sanitary requirements. Each 10' length of conduit is threaded at both ends and supplied with one coupling.
Product Type	Cond 1-1/2" 304

### Manufacturer Information

Brand	Robroy Stainless
GTIN	00784011900442
Manufacturers Part Number	CND304-150
UPC	784011900442

### Taxonomies, Classifications, and Categories

Category Description	Stainless Steel EMT Conduit
Type	CONDUIT



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Trade Size

Trade Size ..... 1-1/2

## Availability

minimum qty ..... 10

## Packaging

Carton ..... 10

Weight ..... 2.77

Weight Per foot ..... 277

## Uses, Certifications, and Standards

standard ..... UL 6A, E98405, CSA C22.2 No. 45.2-08