

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



S41010CT00 1" SS304 Rigid Conduit, 10' W/Coupling Calbrite

Catalog Number	S41010CT00
Manufacturer	Calbrite
Description	Rigid Stainless Steel 304 Conduit With Coupling 1" Trade Size 10 Feet Long
Weight per unit	16.1 (lbs/each)
Product Category	Galvanized Heavy Wall Conduit
Features	
Inside Diameter	1.05
Material	Stainless Stool 2041
outside diameter	1.315
Wall Thickness	0.132
Material, Color, and Finish	
Color	Polished Silver
Finish	#4 Delials ad Cialals
Dimensions and Weight	
Length	120
Descriptions	
Description	1" SS304 RIGID CONDUIT, 10' W/COUPLING
extra long description	CAL S41010CT00 1" X 10' SS304 CONDU
Features	Stainless conduit is specified in corrosive applications that exceed
routuros	the limitations of aluminum, fiberglass, rigid steel, PVC, and PVC
	coated conduit. Type 304 and 316 UL-listed stainless steel
	conduit meets and exceeds current requirements for wash down
	and harsh/corrosive environments and satisfies the strictest
	mandates for plant cleanliness by various state agencies and hundreds of common regulatory requirements.
Long Description	Rigid Stainless Steel 304 Conduit With Coupling 1" Trade Size 10
D. I. I.T.	Feet Long
Product Type	1" X 10' SS304 Conduit W/ Coupling
Short Description	SS_RGD_304
Manufacturer Information	
Brand	CALBRITE
GTIN	00847656000035
Manufacturers Part Number	S41010CT00
UPC	847656000035



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 936-560-4685

TTO BOILTONEOWOI	0000,	- Caanty	i ioaaoto,	∽ .	OI OOI IGI	00.110

Taxonomies, Classifications, and Cate Category Description	gories Stainless Rigid Conduit				
Туре	RIGID				
Trade Size Trade Size	1				
Availability minimum qty	10				
Packaging Carton	10				
Package	50				
Weight	1.61				
Weight Per foot	16.1				
Uses, Certifications, and Standards					
Temperature Rating	1600				