

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## SHC1042CR Cordcon, STR ML, .75-.88", 1", Nyl, Gy Hubbell Wiring Devices

Catalog Number	SHC1042CR		
Manufacturer	Hubbell Wiring Devices		
Description	Kellems Wire Management, Cord Connectors, Straight Male, .75"88", 1", Nylon		
Weight per unit	0.0530 (lbs/each)		
Product Category	Cable & Cord Grips		
Features			
Number of Conductors	Single		
pallet quantity	-		
Material, Color, and Finish			
Color	Gray		
Color Code	Orchid		
<b>Dimensions and Weight</b>			
Size	1.88 in x 1.88 in x 2.45 in		
Descriptions			
_	escription CORDCON, STR ML, .7588", 1", NYL, GY		
extra long description			
Features	Cord Connectors - Hubbell has the broadest line and the widest choice of materials in the industry. NPT hub sizes from ¼" to 3" in straight male end, 90°, 45°, female and underground feed connectors. They are available in your choice of aluminum, plated steel, nylon and stainless steel. The zinc-plated steel cord connectors offers the strength of steel and the corrosion resistance of zinc-plating. These heavy-duty connectors hold up to most manufacturing chemicals including acid solutions, solvents and oth		
Long Description	Kellems Wire Management, Cord Connectors, Straight Male, .75"88", 1", Nylon		
Product Type	Cordcon, STR ML, .7588", 1", Nyl, Gy		
Special Features	Standard Product		
Manufacturer Information			
Brand	WIRING DEVICE-KELLEMS		
GTIN	00783585208145		
Manufacturers Part Number	SHC1042CR		
series	Standard Duty		
UPC	783585208145		



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Tawanamiaa	Classifications	a .a al	Catamarias
Taxonomies.	Classifications	, and	Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Туре	STRAIGHT MALE

### **Packaging**

Maging		
Carton	1	
Package	15	
Weight Per each	0.053	

#### Uses, Certifications, and Standards

Application	Straight Male- Form 4
environmental conditions	Suitable for use in wet locations when used with a listed nylon
	washer between box and fitting.
Mounting	Locknut or Tapped Opening
nema rating	12;13;4;4X
standard	UL Listed