

## **Product Description**

Power equipment oil is a 40/50 to 1 oil designed to withstand high heat which is encountered in small horsepower engines (25 horsepower or less) work in injector or fuel lubricant engines.

## **Product Specifications**

**Applications** For engines of 25 horsepower or less such as:

Not Regulated

Not Regulated

2-Cycle Motorcycles, Motor Scooters, Mopeds, Mini-Bikes, Lawn Mowers, Chain Saws, Garden Equipment, Power Generators, Auxiliary Pumps,

and Refrigeration Equipment

Unit Package Description 15 Ounce Bottle
Generic Description 1 Universal 2-Cycle Oil

Brand Sta-Lube
Net Fill 15 FI Oz

**UPC Code** 0 72213 22610 2

Unit Dimensions-Inches 7.56H x 1.63W x 3.75D

Units Per Case 12

Case Dimensions-Inches 6.5H x 10.25W x 13D

Cases Per Pallet133Lbs. Per Case13

I 2 of 5 Code30072213226103AppearanceBlue Oily LiquidOdorFaint Petroleum

Flashpoint - TCC Method >151°F

Specific Gravity 0.883

Flammability Combustible

Plastic Safe Yes

DOT Proper Shipping Name Not Regulated

VOC % (Federal) 14 VOC g/L (Federal) 124 VOC Lbs./Gal. (Federal) 1.09

VOC Compliant For CA
VOC Compliant For OTC/

LADCO

VOC Category/Limit Not Regulated



## **Product Description**

Power equipment oil is a 40/50 to 1 oil designed to withstand high heat which is encountered in small horsepower engines (25 horsepower or less) work in injector or fuel lubricant engines.

## **Product Specifications**

**Applications** For engines of 25 horsepower or less such as:

Not Regulated

Not Regulated

2-Cycle Motorcycles, Motor Scooters, Mopeds, Mini-Bikes, Lawn Mowers, Chain Saws, Garden Equipment, Power Generators, Auxiliary Pumps,

and Refrigeration Equipment

Unit Package Description 15 Ounce Bottle
Generic Description 1 Universal 2-Cycle Oil

Brand Sta-Lube
Net Fill 15 FI Oz

**UPC Code** 0 72213 22610 2

Unit Dimensions-Inches 7.56H x 1.63W x 3.75D

Units Per Case 12

Case Dimensions-Inches 6.5H x 10.25W x 13D

Cases Per Pallet133Lbs. Per Case13

I 2 of 5 Code30072213226103AppearanceBlue Oily LiquidOdorFaint Petroleum

Flashpoint - TCC Method >151°F

Specific Gravity 0.883

Flammability Combustible

Plastic Safe Yes

DOT Proper Shipping Name Not Regulated

VOC % (Federal) 14 VOC g/L (Federal) 124 VOC Lbs./Gal. (Federal) 1.09

VOC Compliant For CA
VOC Compliant For OTC/

LADCO

VOC Category/Limit Not Regulated