



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

600 E 23rd Street
66046-0000, KS Lawrence
Phone: 785-330-9441
Fax: 785-371-0291



SWB5 3/4 Expl-PRF Box *Hubbell--Killark*

Catalog Number	SWB5
Manufacturer	Hubbell--Killark
Description	SWB Series - Aluminum Feed-Thru Single-Gang Device Body For Use With XCS/XS/XT Cover Assemblies - Hub Size 3/4 Inch - 5-7/8 Inch X 3 Inch X 2-1/4 Inch
Weight per unit	1.3 (lbs/each)
Product Category	Junction, Surface, & Back Boxe

Dimensions and Weight

Size	7.875 in x 3.5 in x 3.5 in
------	----------------------------

Descriptions

Description	3/4 EXPL-PRF BOX
extra long description	KLRK SWB-5 3/4" 5 7/8X6 1/2X2 1/4 B
Long Description	SWB Series - Aluminum Feed-Thru Single-Gang Device Body For Use With XCS/XS/XT Cover Assemblies - Hub Size 3/4 Inch - 5-7/8 Inch X 3 Inch X 2-1/4 Inch
Product Type	3/4" 5 7/8X6 1/2X2 1/4 Bdy Fdthru
Special Features	Killark SWB SERIES CONTROL STATION BACK BOXES provide control solutions in hazardous location areas to supply;START/STOP Motor Functions, LED Pilot Light Indications and more for use with Killark XCS and XS Cover Assemblies. For use in Class 1 Division 1 & 2, Class 1 Zone 1 & 2 areas for indoor use and are Non-Factory Sealed requiring the need for a conduit seal fitting. UL Listed and CSA Certified. The SWB is offered in a wide variety of configurations from 1/2" to 1" dead end and feed through for single

Manufacturer Information

Brand	KILLARK
GTIN	00783936630052
Manufacturers Part Number	SWB-5
series	SWB Series
UPC	783936630052

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Aluminum device body

Packaging

Carton	1
Package	5
Weight Per each	1.26



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

600 E 23rd Street
66046-0000, KS Lawrence
Phone: 785-330-9441
Fax: 785-371-0291

Uses, Certifications, and Standards

Application

Hazardous locations due to the presence of flammable gases or vapors, combustible dusts, or easily ignitable fiber or flyings. Installations at petroleum refineries, chemical and petrochemical plants, and other processing or storage facilities where similar hazards exist. Use in conjunction with magnetic starters or contactors for remote control of motors.

Enclosure

Aluminum enclosure

environmental conditions

Hazardous locations

Mounting

WALL

standard

UL, CSA