



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## T0030 30A 125V TD Edison Base Plug Fuse

Littelfuse

Catalog Number	T0030
Manufacturer	Littelfuse
Description	Littelfuse Plug Fuses Provide Overcurrent Protection to General Purpose Circuits and Small Motor Loads. Edison-Base Plug Fuses (Too and Tlo Series) Feature Metal Threads Similar to Incandescent Lamp Bases. Type S Plug Fuses (Soo and Slo Series) Utilize A Nonmetallic Threaded Base and Must Be Used With Type S Adapters (Sao Series). The National Electrical Code Permits Edison Base Plug Fuses to Be Used For Replacement Purposes Only. Type S Fuses and Adapters Prevent Shunting Open Fuses and Over-Fusing.
Weight per unit	0.2500 (lbs/each)
Product Category	Plug Fuses & Adapters

### Descriptions

Description	30A 125V TD EDISON BASE PLUG FUSE
extra long description	LFSE TOO030 FUS 125V T/D PLUG 30A E
Long Description	Littelfuse Plug fuses provide overcurrent protection to general purpose circuits and small motor loads. Edison-base Plug fuses (TOO and TLO series) feature metal threads similar to incandescent lamp bases. Type S Plug fuses (SOO and SLO series) utilize a nonmetallic threaded base and must be used with Type S adapters (SAO series). The National Electrical Code permits Edison base Plug fuses to be used for replacement purposes only. Type S fuses and adapters prevent shunting open fuses and over-fusing.
Product Type	Fus 125V T/D Plug 30A Edison-Bas
Special Features	Metal threads

### Manufacturer Information

Brand	Littelfuse
GTIN	00079458430738
Manufacturers Part Number	TOO030
UPC	079458430738

### Taxonomies, Classifications, and Categories

Category Description	PLUG FUSES
Type	Time Delay Fuse



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Package	4
Weight Per each	0.25

## Uses, Certifications, and Standards

Application	General purpose circuits and small motor loads
-------------	--