


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





GTIN

UPC

Manufacturers Part Number

T17SA 1/2" Alu T FM7 Conduit Rody

Catalog Number	T17SA
Manufacturer	Crouse Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 7 Conduit Outlet Body Copper-Free Aluminum, T Shape, 1/2"
Weight per unit	
Product Category	Alum
Features	
dimensions	5.6300 IN X 1.7500 IN X 2.4400 IN
Form	Form 7
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	1-3/4
Hub Size	
Length	F F /0
Width	2-7/16
Descriptions	
Description	1/2" ALU T FM7 CONDUIT BODY
extra long description	CRS-H T17 SA 1/2 T AL FORM 7 CNDT B
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 7 bodies are offered in 11 different shapes to provide the most flexible offering on the market. Form 7 Condulet outlet bodies approach conduit in size for neat, compact installations. Many shapes and sizes are available for rigid threaded conduit. Our Form 7 family features an exclus
Long Description	Eaton Crouse-Hinds series Condulet Form 7 conduit outlet body, Copper-free aluminum, T shape, 1/2"
Product Type	·
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES

00782274626154

782274626154

T17 SA



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging Carton	1
Package	5
Weight Per each	0.49
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Condulet

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D