ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685



T2535183S 25KVA 1PH 480/240 DRY TYPE TRANSFORMER

HUBBELL INCORPORATED DELAWARE

Catalog Number	T2535183S
Manufacturer	HUBBELL INCORPORATED DELAWARE
Description	Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 25kVA
Weight per unit	260.0 (lbs/each)
Product Category	Single Phase Non Ventilated To

Features

Fuse Rating	Primary: 150 AMP For 240 V, 70 AMP For 480 V, Secondary: 300 AMP For 120 V
Primary Voltage	240 X 480
Secondary Voltage	120/240
Pallet Quantity	4
Product Category	Dry Type Distribution Transformer

Dimensions and Weight

Height	18.44
Length	13.34
Width	16.13

Descriptions

Construction	ENCAPSULATED
Description	25KVA 1PH 480/240 DRY TYPE TRANSFORMER
Long Description	Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 25kVA
Product Type	TFMR 1PH 25KVA 240X480-120/240
	Dry Type Distribution Transformer
Special Features	Encapsulated core and coil; Shielded for cleaner power; Encapsulated and completely enclosed design electrical grade silica and resin compounds completely enclose the core and coil to seal out all moisture and air, UL type 3R enclosure for indoor or outdoor service, encapsulation eliminates corrosion and insulation deterioration; Quiet operation with sound levels well below NEMA standards; 10-year limited warranty
Extra Long Description	ACME T2535183S TFMR 1PH 25KVA 240X4

Manufacturer Information

Brand	Acme Electric, a Hubbell affiliate
	ACME ELECTRIC
GTIN	00047503734209
Manufacturers Part Number	T2535183S
UPC	565656

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Taxonomies, Classifications, and Categories

Category Description	1 PHASE TRANSFORMERS
Type	Distribution Transformer

Packaging

Carton	1
Weight Per Each	260.0 (lbs/each)

Uses, Certifications, and Standards

Enclosure	NEMA 3R Steel
Mounting	WALL
Temperature Rating	115 DEG C Rise
Standard	UL 506, UL File Number E79947V1, UL Control Number 50B8, UL Insulation Number H3221, CSA Certified, OSHA Compliant, ANSI, IEEE



* Representative image

T2535183S

by Acme Electric
Catalog ID: T2535183S

Prop65_Cancer&Reproductive

Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 25kVA

- Quite operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

Product Details

General

ANFC Taps	2
BNFC Taps	4
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	240 X 480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	120/240 V
Taps % Steps	2.5%
UL Insulation Class	180°C
UPC	047503734209
Winding Material	CU
kVA	25

Dimensions

Height	18.44 in
Length	13.34 in
Weight	250 lb
Width	16.13 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240 X 480 V

Certifications and Compliance

CSA Standard	C22.2 No. 47

Nema Rating	NEMA 3R
UL Standard	UL 506