

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## T400M 4" T FM5 CNDT Body Crouse-Hinds

Catalog Number	T400M
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Conduit Outlet Body, Malleable Iron, T Shape, 4"
Weight per unit	N/A
Product Category	Bodies & Covers
Features	
dimensions	18.1300 IN X 5.5600 IN X 7.1500 IN
Form	Form 5
Material, Color, and Finish Finish	Hot Dip Galvanized
Dimensions and Weight	
Height	5.56
Hub Size	4 in
Length	18.13
Width	7.15
Descriptions	
Description	4" T FM5 CNDT BODY
extra long description	CRS-H T400M 4 FORM 5 T COND BODY MA
Features	Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 conduit outlet body, Malleable iron, T shape, 4"
Product Type	4 Form 5 T Cond Body Malleable
Special Features	Weight 2542 Lb per 100



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	Crouse-Hinds
GTIN	00782274756325
Manufacturers Part Number	T400M
UPC	782274756325
Taxonomies, Classifications, and Cat	tegories
	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	1
Weight Per each	0
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
Enclosure	Condulet
standard	UL 514B, CSA C22.2, CUL