

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

T68 2" T FM8 Conduit Body Crouse-Hinds

Catalog Number	T68
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Conduit Outlet Body,
	Feraloy Iron Alloy, T Shape, 2"
Weight per unit	
Product Category	Bodies & Covers
Features	
dimensions	12.2500 IN X 3.5600 IN X 5.0000 IN
Form	Form 8
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	3-9/16
Hub Size	
Length	12-1/4
Width	5
Descriptions	
Description	2" T FM8 CONDUIT BODY
extra long description	CRS-H T68 2 T FORM 8 CNDT OUTLET BO
Features	One hundred years after the introduction of the Condulet, Eaton
	remains the leader in conduit outlet bodies with its Crouse-Hinds
	series. The line has grown to six families manufactured in a
	variety of materials, and Form 8 bodies are offered in seven
	different shapes to provide the most flexible offering on the
	market. Form 8 Condulet outlet bodies provide more room for
	heavier conductors. Many shapes and sizes are available for rigid
	threaded conduit. Two cover screws on all body sizes provide tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 conduit outlet body,
Long Description	Feraloy iron alloy, T shape, 2"
Product Type	2 T Form 8 CNDT Outlet Body
Manufacturer Information	
Brand	Eaton
GTIN	00782274628202

782274628202 Taxonomies, Classifications, and Categories

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	7.9
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Condulet
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D