ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685



T70ICWH INSIDE CORNER

PANDUIT CORPORATION

Catalog Number	T70ICWH
Manufacturer	PANDUIT CORPORATION
Description	The inside corner fitting is used to join sections of T-70 raceway at inside corners while maintaining proper separation of data and power. It is White.
Weight per unit	1.0 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

Features

Cover Type	Inside Corner
Material	PVC
Media	Yes

Dimensions and Weight

Height	3.00
Length	NA
Width	3.5

Descriptions

Description	INSIDE CORNER
Long Description	The inside corner fitting is used to join sections of T-70 raceway at inside corners while maintaining proper separation of data and power. It is White.
Product Type	Surface Raceway, T-70 Inside Corner, White
Extra Long Description	PAN T70ICWH Surface Raceway, T-70 I

Manufacturer Information

Brand	PANDUIT
	Panduit®
GTIN	00074983630707
Manufacturers Part Number	T70ICWH
UPC	981002

Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Type	Surface Raceway Corner Fitting

2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Packaging

Carton	1
Package	10
Weight Per Each	1.0 (lbs/each)

Uses, Certifications, and Standards


Application	Provides Solutions for Routing Low Voltage, Fiber Optic and/or Power Cabling Along Perimeter Walls.T-70 Features the Workstation Outlet Center ™ Offset Box, Which Provides an Offset Solution to Maximize Channel Capacity and Outlet Density.
Standard	CE Compliant, UL5A Listed, UL Listed 95425, UL Listed E116129

Pan-Way® T-70 Surface Raceway System

PANDUIT®
SPECIFICATION SHEET

specifications

T-70 non-metallic multi-channel capable surface raceway shall be used to route, protect, and conceal data, voice, video, fiber optic and power cabling. The raceway shall be listed as suitable for use in applications up to 600 volts between conductors by Underwriters Laboratories, Inc. per standard 5A, and by Canadian Standards Association, Inc. per 22.2 no. 62.1-03, when screw secured and installed per instructions. A full complement of fittings with a 1" minimum bend radius compliant with TIA/EIA-568-B, must be available as well as device brackets and internal junction boxes to install a variety of communication and electrical devices. Divider walls must be available to form separate channels in the multi-channel raceway. Snap-on faceplates for data and power terminations shall be available. An offset box shall be available, with versions for Snap-on as well as screw mount faceplates, for mounting the power receptacle outside of the raceway channel. T-70 raceway will be manufactured from impact-resistant material with flammability rating of V-0. T-70 raceway must be tamper resistant yet, also allow access for moves, adds and changes. T-70 raceway finish shall be pure color and will resist scratches and dents and will not peel or corrode. T-70 raceway shall be available in four standard colors and shall be optimized for use with the Pan-Net Communication System.



technical information

Material:	Rigid PVC
Flammability:	UL94V-0; FT4
Voltage rating:	UL-5A 600VAC; CSA C22.2 No. 62.1-03 600 V
Safety compliance:	UL Listed 95425 (raceway); UL Listed E116129 (fittings)
NEC:	Article 388
Color:	Off White (IW), Electrical Ivory (EI), White (WH)
CSI spec form:	LP-CSISPEC-T70-1

key features and benefits

1" bend radius control fittings:	Reduces time required for planning, designing, procurement, and installation, resulting in simpler specification and up to 75% faster implementation
Snap-on faceplates:	Faceplates snap directly onto the raceway base; cabling can be quickly accessed by removing only the faceplate, requiring less labor and cost of maintenance
Channel has a 70mm opening:	Accepts NEMA standard snap-on or screw-on power or communication faceplates from all manufacturers
Highly tamper resistant:	Very difficult for untrained personnel to enter the raceway or remove faceplates; provides maximum security for communication cabling and maximum safety for power cabling
Non-metallic construction:	Lightweight reduces installer fatigue; solid color throughout profile will not chip peel, rust, corrode, or scratch; easy to cut reducing the need for special cutting devices; high impact resistance; durable
Designer profile:	Aesthetically pleasing and matches a wide variety of decors
Available in three standard colors:	Matches a variety of colors for various applications

applications

Pan-Way T-70 Non-Metallic Surface Raceway is a multi-channel channel raceway which provides solutions for routing low voltage, fiber optic and/or power cabling along perimeter walls. T-70 raceway can mount NEMA standard screw-on faceplates or superior Pan-Way Snap-on Faceplates directly to the channel. T-70 features the Workstation Outlet Center™ Offset Box, which provides an offset solution to maximize channel capacity and outlet density.

Pan-Way T-70 Raceway	
Raceway Base	
6 feet:	T70BIW6
8 feet:	T70BIW8
10 feet:	T70BIW10
Raceway Cover	
6 feet:	T70CIW6
8 feet:	T70CIW8
10 feet:	T70CIW10
Divider Wall	
6 feet:	T70DW6
8 feet:	T70DW8
10 feet:	T70DW10
T-70 Raceway Fittings and Accessories	
Base coupling:	T70BCIW-X
Cover coupling:	T70CCIW-X
Outside corner fitting:	T70OCIW
Inside corner fitting:	T70ICIW
Right angle fitting:	T70RAIW
End cap fitting:	T70ECIW
Entrance end fitting:	T70EEIW
Tee fitting:	T70TIW
Insert for tee fitting:	T70TD
Transition fitting base/cover:	T70TRIW
Transition fitting cover only:	T70TRCIW
Wire retainer:	T70WR-X
Device bracket:	T70DB-X
Standard faceplate bracket:	T70SDB-X
Three-sided hanging box:	T70HB3-X
Hanging box:	T70HB-X
Workstation Outlet Center Offset Box:	T70WCIW
Workstation Outlet Center Offset Box:	T70WC2IW


For standard colors other than IW (Off White), replace IW in part number with EI (Electrical Ivory), or WH (White).

wire fill


Raceway Type and Configuration	Fill Area (in²)	Electrical Cables			Data Grade Cables								Coax Cables				Fiber Optic Cable	
		14 AWG	12 AWG	10 AWG	24 AWG		23 AWG		26 AWG		23 AWG							
		THHN/THWN/T90			Cat. 5e		Cat. 6		Cat. 6A (SD)		Cat. 6A		RG6		RG59/u		2 Strand	
		0.111	0.130	0.164	DIA = 0.193		DIA = 0.240		DIA = 0.240		DIA = 0.300		DIA = 0.275		DIA = 0.242		DIA = 0.175	
		FILL			FILL		FILL		FILL		FILL		FILL		FILL		FILL	
		MAX	MAX	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX
		(UL Temp Rise Test)			(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)
T-70: No Devices	5.15	24	20	15	70	105	45	68	45	68	29	43	34	52	44	67	85	128
T-70: Power and data using the three-sided hanging box and device bracket	0.86	14	11	7	–	–	–	–	–	–	–	–	–	–	–	–	–	–
	1.72	–	–	–	23	35	15	22	15	22	9	14	11	17	14	22	28	42
T-70: Data only (Screw-on Faceplates)	3.67	–	–	–	50	75	32	48	32	48	20	31	24	37	31	47	61	91
T-70: Data only (Snap-on Faceplates)	4.71	–	–	–	64	96	41	62	41	62	26	39	31	47	40	61	78	117
T-70: Power and data using the Workstation Outlet Center™ Offset Box	0.91	14	11	7	–	–	–	–	–	–	–	–	–	–	–	–	–	–
	3.12	–	–	–	42	63	27	41	27	41	17	26	21	31	27	40	51	77

Note: For all cable options please see the Raceway Cable Fill Calculator on www.panduit.com/calculators.

t-70 raceway




T-70
Internal Area = 5.15 Sq. In.



T70B




T70C




T70DW


fittings and accessories




T70BC-X




T70CC-X




T70OC




T70IC




T70RA




T70EC




T70EE




T70T




T70TD




T70TR
T70TRC




T70WR-X




T70DB-X




T70HB3-X




T70HB-X



T70WC
T70WC2



T70TRI



T70SDB-X

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information
Visit us at www.panduit.com
Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

© 2023 Panduit Corp.
ALL RIGHTS RESERVED.
FRSP34-WW-ENG
3/2023