

# NEER Zinc Gland Compression Connectors and Couplings

For EMT.

## TC-600: Couplings

### Application

- To join lengths of steel EMT for concretetight, dry or damp location applications.

### Features

- Concretetight.
- Raintight (wet locations) Canada.

### Material/Finish

- Zinc die cast

### Certifications and Compliances

- UL Standard: 514B
- UL Listed: E35001
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1

## TC-600: Connectors

### Application

- To secure and terminate steel EMT to knockouts in concretetight box, dry or damp location applications.

### Features

- Male hub threads — NPS.
- Concretetight.
- Available with insulated throat.
- Furnished with locknut.

### Material/Finish

- Zinc die cast

### Certifications and Compliances

- UL Standard: 514B
- UL Listed: E35001
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1



TC-611



TC-601

Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters	
		Body Length	Maximum Diameter
1/2	TC-611	1.70/43.2	0.98/24.9
3/4	TC-612	1.78/45.2	1.21/30.7
1	TC-613	1.82/46.2	1.52/38.6
1-1/4	TC-614	2.12/53.8	1.83/46.5
1-1/2	TC-615	2.35/59.7	2.13/54.1
2	TC-616	2.47/62.7	2.55/64.8
2-1/2	TC-617 *	3.28/83.3	3.30/83.8
3	TC-618 *	3.35/85.1	3.94/100.1
3-1/2	TC-619 *	3.54/89.9	4.97/126.2
4	TC-620 *	3.54/89.9	4.97/126.2

Trade Size (Inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches/Millimeters		
			Body Length	Thread Length	Maximum Diameter
1/2	TC-601	TCI-601	1.26/32.0	0.40/10.2	0.98/24.9
3/4	TC-602	TCI-602	1.29/32.8	0.40/10.2	1.21/30.7
1	TC-603	TCI-603	1.44/36.6	0.43/10.9	1.52/38.6
1-1/4	TC-604	TCI-604	1.74/44.2	0.63/16.0	1.83/46.5
1-1/2	TC-605	TCI-605	1.86/47.2	0.65/16.5	2.13/54.1
2	TC-606	TCI-606	2.15/54.6	0.73/18.5	2.55/64.8
2-1/2	TC-607 *	TCI-607 *	2.62/66.5	0.91/23.1	3.30/83.8
3	TC-608 *	TCI-608 *	2.69/68.3	0.96/24.4	3.94/100.1
3-1/2	TC-609 *	TCI-609 *	2.84/72.1	0.96/24.4	4.97/126.2
4	TC-610 *	TCI-610 *	2.84/72.1	0.96/24.4	4.97/126.2

\* For EMT and threadless rigid metal conduit and IMC.

Commercial Products

COMMERCIAL PRODUCTS: EMT FITTINGS

# NEER Zinc Gland Compression Connectors and Couplings

For EMT.

## TC-600: Couplings

### Application

- To join lengths of steel EMT for concretetight, dry or damp location applications.

### Features

- Concretetight.
- Raintight (wet locations) Canada.

### Material/Finish

- Zinc die cast

### Certifications and Compliances

- UL Standard: 514B
- UL Listed: E35001
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1

## TC-600: Connectors

### Application

- To secure and terminate steel EMT to knockouts in concretetight box, dry or damp location applications.

### Features

- Male hub threads — NPS.
- Concretetight.
- Available with insulated throat.
- Furnished with locknut.

### Material/Finish

- Zinc die cast

### Certifications and Compliances

- UL Standard: 514B
- UL Listed: E35001
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1



TC-611



TC-601

Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters	
		Body Length	Maximum Diameter
1/2	TC-611	1.70/43.2	0.98/24.9
3/4	TC-612	1.78/45.2	1.21/30.7
1	TC-613	1.82/46.2	1.52/38.6
1-1/4	TC-614	2.12/53.8	1.83/46.5
1-1/2	TC-615	2.35/59.7	2.13/54.1
2	TC-616	2.47/62.7	2.55/64.8
2-1/2	TC-617 *	3.28/83.3	3.30/83.8
3	TC-618 *	3.35/85.1	3.94/100.1
3-1/2	TC-619 *	3.54/89.9	4.97/126.2
4	TC-620 *	3.54/89.9	4.97/126.2

Trade Size (Inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches/Millimeters		
			Body Length	Thread Length	Maximum Diameter
1/2	TC-601	TCI-601	1.26/32.0	0.40/10.2	0.98/24.9
3/4	TC-602	TCI-602	1.29/32.8	0.40/10.2	1.21/30.7
1	TC-603	TCI-603	1.44/36.6	0.43/10.9	1.52/38.6
1-1/4	TC-604	TCI-604	1.74/44.2	0.63/16.0	1.83/46.5
1-1/2	TC-605	TCI-605	1.86/47.2	0.65/16.5	2.13/54.1
2	TC-606	TCI-606	2.15/54.6	0.73/18.5	2.55/64.8
2-1/2	TC-607 *	TCI-607 *	2.62/66.5	0.91/23.1	3.30/83.8
3	TC-608 *	TCI-608 *	2.69/68.3	0.96/24.4	3.94/100.1
3-1/2	TC-609 *	TCI-609 *	2.84/72.1	0.96/24.4	4.97/126.2
4	TC-610 *	TCI-610 *	2.84/72.1	0.96/24.4	4.97/126.2

\* For EMT and threadless rigid metal conduit and IMC.