



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



TCF20RN Cubefuse TCF 20A Non-Ind *Bussmann Fuses*

Catalog Number	TCF20RN
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series TCF Fuse, 20 A, 60 HZ, 50 HZ, Dual, CF, Black, Time Delay, Class CF, 10 Sec At 500%, 100 Kaic At 300 VDC, 300 Kaic At 600 V, Glass Filled Pes, 35 MM Din Rail, Chassis, 600 V, 300 VDC
Weight per unit	1.0 (lbs/each)
Product Category	Tools & Testers

Features

amperage rating	20 A
class	Class CF
connection	Blade End
dimensions	1.8800 IN X 0.7500 IN X 1.7500 IN
element	Dual
interrupt rating	300 kAIC at 600 Vac 100 kAIC at 300 Vdc
Material	Glass Filled PES
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

Descriptions

Description	CUBEFUSE TCF 20A NON-IND
extra long description	BUSS TCF20RN CUBEFUSE, TCF 20A NON-
Features	The revolutionary Bussmann™ series Low-Peak™ CUBEFuse™ delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful. And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann series TCF fuse, 20 A, 60 Hz, 50 Hz, Dual, CF, Black, Time delay, Class CF, 10 sec at 500%, 100 kAIC at 300 Vdc, 300 kAIC at 600 V, Glass filled PES, 35 mm DIN rail, Chassis, 600 V, 300 Vdc
Product Type	Cubefuse, TCF 20A Non-Ind
Special Features	Finger Safe



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712220941
Manufacturers Part Number	TCF20RN
UPC	051712220941

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

Carton	1
Package	12
Weight Per each	1.01

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security SystemsDatacenters - Facilities: Power DistributionCommercial / Institutional Buildings / Structures - Critical PowerInd Facilities & Factories - Facility: Power Distribution and ControlStationary Machinery and Equipment Outside Factory - HVAC
Mounting standard	35 mm DIN Rail, Chassis UL Listed,CSA Certified,RoHS Compliant,CE Marked